

Base Weight:	10,220	22.5 ANR 22.5 Ton Tandem Air Tilt/No Ramp Tags
TRAILER		
	Overall Length	34 ft. 7 in
	Overall Width	102 in.
	Weight lbs +/- 2%	10333, including options
	A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
	Hitch	3 in. pintle eye, adjustable 7 position, 15 in. to 28 1/2 in.
DECK		
	Deck Length	<u>21 ft.</u>
	Loaded Deck Height	34 in.
	Main Frame	Hi-Tensile Wide Flange 14 in. @ 26
	Cross Members	Hi-Tensile 6 in. Channel @ 8.2
	Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside
	Air Tilt Deck	*NPO*: * 4 Air Bags
	Floor	1 3/8 in. x 7 in. Keruing Shiplapped
	Landing Gear	Dual Holland Mark V 2 Speed
	Rear	Wedge Style bumper with air assisted tilt deck for ground loading
	Step	*NPO*: Bolt on, Located on Front Corner of deck, Driver side , and 1 Step on Passenger Side in front of Lead Axle
SUSPENSION/A	XLES	
	Axles	25,000 lbs Capacity 77.5 in. Track
	Spread	49 in.
	Suspension	Heavy Duty spring ride
	Alum Air Tank	*NPO*: Drain Plug with Cable
	Brakes	Quick Change 12 1/4 in. x 7 in.
	Brake Chamber	#3030, All Axles
	Air Brake System	2S/1M
	Air Tank(s)	Aluminum
	Bearings	Oil Bath
	Slack Adjusters	Automatic
	Hubs & Drums	8 Stud Unimount C / W Cast Drums
	Tires	235/75R17.5 16 ply
	Wheels	Alum. Wheel Pkg. 17.5 (4 Steel, 4 Polished)
BEAVERTAIL		
	Length	6 ft. @ 8 degree slope, Self Cleaning Outside, Planked in inside
GENERAL SPEC	FICATIONS	
	Electrical System	Modular, Vapor Proof GROTE Ultra Blue
	Lights	LED CMVSS 108 / FMVSS 108
	Lights	Amber Flashing Strobe Lights (Mounted in Bumper)
	Front Connector	SAE J560 7 Pin
	Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
	Color	Black

Mudflaps	1 set of BWS at rear
Toolbox	Full A Frame mounted with solid bottom and cover
Load Securement	9 pair of D-rings: 7 pr on main deck evenly spaced, 1 pr on main beam at headboard 1 pr on top of A Frame on both sides of toolbox
Fenders	3/16 in. deck plate
	GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

٦

DISCLAIMER