

 	A029540-A029552 VIN: 77253-77256		SALES RENTALS PARTS SERVICE			
	Allentown, PA: 800-383-8894 Baltimore, MD: 888-601-7500 Concord, NC: 800-438-2250 Delmar, DE: 866-486-1400 Des Moines, IA: 888-673-5011 Elkton, MD: 800-544-7127 Jacksonville, FL: 800-828-3055	Little Rock, AR: 833-424-8944 Portland, ME: 800-325-4253 Raleigh, NC: 833-418-9777 Scranton, PA: 800-569-1400 Springfield, MA: 800-854-5306 Voorhees, NJ: 866-315-0235 Walpole, MA: 800-854-5310				
	haletrailer.com @haletrailer     					
	800-232-6535 *FINANCING AVAILABLE					

Trailer Model: FB8X45SS-OTR-70H

Axle: 30,000 lb.

Tire: 295/75R-22.5

Color: Black

Special Instructions:

Crane counterweight trailer
 Custom fabricated main beam construction (80 KSI web w/ 100 KSI beam flanges)
 45' overall length
 102" wide x 10' long upper wood deck w/ rub rail and stake pockets
 33' lower open deck
 (2) 30,000 lb. AXN air brake axles
 Hutch 9700 spring suspension w/ 54.5" axle spacing
 Upgrade to 295/75R-22.5" dual tire and wheel assemblies
 Bendix ABS air kit
 40" deck height
 3 lb. grating welded on lower deck in areas not occupied by counterweights
 (2) bolt-on steps for accessing lower deck - (1) on each side
 (2) sets of pin housings to lock counterweights all on lower deck w/ high locking position only - housings in front and rear
 (12) 1" bent D-rings on lower deck - (2) sets for each counterweight location
 (2) Boom rests - (1) at rear of upper wood deck and (1) at rear of lower deck
 Single poly fenders on rear axles
 Dual Jost A420 semi-style landing gears **w/ low-profile sand shoes**
 Axles, 71.5" Track w/ 54.5" Closed Axle Spacing

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.