



A029547-A029548 VIN: 46912-46913

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: Walpole, MA: 800-828-3055 800-854-5310

Base Model #: DC48 x 102 3Axle

Serial #: 46912 - 46913 components description

CAPACITY Heavy Duty Package - 120,000 lbs. GVWR (110K Eq. Dist. & 90,000 in 10' Span)

OVERALL LENGTH 48' UPPER DECK LENGTH 12'

* * * Minimum Pitch of 2-3/4" * * *

* * * 102" Swing Clearance * * *

LOWER DECK LENGTH 36' (Deck Height-37")

OVERALL WIDTH 8'6"

KING PIN SETTING 18"

UPPER COUPLER PLATE 5/16"

UPPER COUPLER HEIGHT * * 50" * *

BULKHEAD None

MAINFRAME 26" Fabricated - PreCambered I-Beams - Heavy Duty

* * Main Beams 3/4" x 6 Top and Bottom, 1/4" Webs Throughout, Lower Deck, 1/4 Rear Section, 1/4"

Web in Neck. * *

* * Transition Plate * *

No Flip Axle Brackets.

SIDE RAILS 6" Alumumin with Double L Winch Track

FLOOR SILLS 4" I-Beam 12" O.C. HD Pkg (+325#)

FLOOR DECKING 1/4" Aluminum Tread Plate - Counter Sink Screws

Install Upper Deck and Lower Deck (Only Behind Twist Locks).

WINCH TRACK Aluminum Integrated Double L - Both Sides

Tie Bar Both Sides.

WINCHES 12 Double L (6 Per Side)

STRAPS None

LANDING GEAR Two Speed

SUSPENSIONS Hendrickson - 30K Suspension

LIFT AXLE Lift Rear Axle

DUMP VALVE Dump Valve in Box Includes: Manual Override, Liquid Filled Gauges and Lift Axles

** All Air Control valve in Box.**

SCALES Digital Electronic Right Weight In Sealed Box

Calibrate In House.

AXLES (3) 30K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride(Parallel Spindle)

Parallel Spindle.

23K Brake Linings.

AXLE SPACING 54.5" (+30#)

PARKING BRAKES 3 Axle

DUST SHEILDS None

WHEELS Disc - Hub Piloted - 17.5 - Aluminum on all 12 Wheels

All Aluminum Wheels.

TIRES 235/75R 17.5 - 36" Loaded Deck Height - Double Coin

ANTI-SAIL MUD FLAPS Rear Frame

STAKE POCKETS Aluminum 4" - 24" O.C. Side and 5 Across Rear

RUB BAND STEEL Aluminum 3/8" x 3"

PIPE SPOOLS Aluminum Triangle DOCK BUMPERS Rubber Inboard Shop Print - Quote: 85672 Page 2 of 2

DOVETAIL None LOADING RAMPS None TIRE CARRIERS None

CARGO TIE DOWN Container Locks/Twist Locks 20Ft

Install Screw Up Adjustable Twist Locks.

Location For 20ft Container, 12" From Front Edge of Lock to Dash Board.

TOOLBOXES None TOOLBOX TYPE None

LIGHTS Sealed Wiring Harness w/ LED Pkg

PAINT Black - Sherwin Williams Epoxy Primer and Acrylic Polyurethane - Shot Blasted

CUSTOM 1. Strobe Kit- 3-3-3 Toggle Switch - D/S - Rear Trailer

CUSTOM 2. Prep - For Flip Neck Box