

# HALE TRAILER BRAKE & WHEEL



Resale Inventory  
A029605-A029606

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 \*FINANCING AVAILABLE

## Revolution 52 Alum Flat 53' Rear Axle Slide (Model: HAR5222RSA)

**Length / Width:** 53 feet x 102 inches

**Suspension Type:** Rear axle slide; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

**Frame Rating:** 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads

**Flooring:** Knurled extruded 3-1/8 aluminum, **StirLITE Friction Stir Welded Floor** with 2 wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear

**Side Rails:** Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

**Stationary Chain Cargo Tie Downs:** 17 pair - recessed in siderails

**Stake Pockets:** Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)

**Rubrail:** Integrated with side rail

**Main Beams:** Extruded aluminum - 8.25 inch flange

**Kingpin:** 30 inches

**Loaded Fifth Wheel Height:** 49 inches

**Landing Gear:** Jost AX100G19 **ALUMILIGHT Aluminum Landing Gear** with forward & rear bracing

**Bulkheads:** None standard

**Number of Axles:** 2

**Axle Spindle:** Tapered

**Brakes:** Spring brakes, auto slacks, Aluminum air tank

**Air Line Filters:** (2) Meritor In-line type installed

**ABS:** 4S/2M - no cable or tool

**Axle Spread:** 122 inches open - 54 inches closed - Meets California, Canadian RTAC and BC dimensional specifications in closed position

**Hub and Drums:** 10-hole hub-piloted with outboard cast drums - STANDARD

**Wheel Ends:** Grease in hubs - \*\*\* 5-year wheel end warranty \*\*\*

**Wheels:** 22.5 x 8.25 aluminum Lvl One buffed wheels

**Tires:** 11R 22.5 14PR economical OEM standard tires

**Tire Inflation System:** None standard

**Suspension Detail:** Hendrickson air ride

**Air Assist Slide Box Pins:** Standard mount of controls on slider frame

**Auto Glad Hand Dump:** Installed

**Electric Dump Valve:** Wired to 7-way auxiliary socket to dump rear axle

**Front Corners:** Tapered

**Electrical System:** LED: 5 Lights/Side; Rear with 3 4-inch Round Lights/Side, 3 Round Lights Center Cluster

**Other Electrical Specifications:** 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections

**Paint:** Black urethane on steel parts with Revolution decals - STANDARD

**Conspicuity Tape:** Per NHTSA specs - installed in recess on rubrails

**Bumper:** Bolt-On; Meets underide requirements

**Mudflaps:** 1 set OEM standard behind rear axle only

**Spare Tire Carrier:** None standard

**Winch Track:** Dual full-length integrated aluminum -- double L design

**Sliding Winches:** 12 standard; 6 each side; sliding rope hook/ winch strap hook retainers - STANDARD

**27' Winch Straps:** None standard

**30' Winch Straps:** None standard

**Sliding J-Hook for Ring vs. Flat Hook on 4" Strap:** None standard

**Dock Bumpers:** 1 pair rubber on rear

**Hubodometer:** None standard

**Registration Holder:** Install registration holder - OEM standard

**Tool Box:** None standard

**VIN Plate:** Bilingual US/Canadian VIN plate

**Please Note:** Price includes commodity surcharges

**Unit Numbers & Decals:** Not available

\*Aero Conestoga

### DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.