

HALE TRAILER BRAKE & WHEEL



A029629-A029630
VIN: 180216-180217

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Trailer Model:

Kalyn Hydraulic Sliding Axle HSA24050

HSA24050 Standard Equipment

Net Capacity:	40 Tons	80,000 lbs Distributed in 50 ft, 50,000 lbs Concentrated in 10 ft
Nominal:	50 feet OAL	Kingpin to center of rear axle 40 feet in Transport Mode
	8 feet 6 inches Wide	Dump angle 16° Loading angle 7°
GOOSENECK:		
	10'-8" Gooseneck Length (48' & 50') / 11'-6" (53')	SUSPENSION:
	48" Loaded 5th Wheel Height, 18" Kingpin Setting	25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles
	86" Swing Radius (48' & 50') / 96" Swing Radius (53')	50" axle spacing 71" track
	20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable	12-1/4" x 7-1/2" Brakes ABS Module: 2S1M
	Work lights on the winch 2 Tool compartments	Auto Slack Adjusters and Spring Brakes on all Axles
	Wet Kit: Trailer Operation; 3/4" Hydraulic Couplings	6.75 x 17.5 Hub Piloted Disc Wheels
	Integrated Tool Box in Neck W/ Steel Hinges and Door	235/75 R 17.5 16PR Tires Manual Dump Valve
	2-Speed Landing Gear, Crank Handle Roadside	Suspension: Ridewell or Equivalent Air ride Air Ride
DECK:		
	NOM Deck Length: 39.34 ft NOM Deck Width: 102 in	Alignment Bracket for Sliding Suspension
	Loaded Deck Height: 37 in	GENERAL:
	4 Beam design - 100,000 psi yield flanges & 80,000 web minimum	12 Volt System with 7 way Sealed Harness
	14" tall main beams and 15" tall side rails	DOT Rubber Mounted Sealed Beam LED Lights
	4" I-beam cross members on 9" Centers, 1-3/8" Apitong Deck(full width)	Epoxy Primer & Black Polyurethane Paint
	Double Key Hole Chain Slots in Upper Flange on 36" Centers	2 Function Wireless Remote for Winch
	Double Key Hole Chain Slots Along Center of Deck on 36" Centers	Heavy Duty DOT Approved Bumper KS Mud Flaps
	Reinforced Rear Approach Plate with 6 Chain Slots	Red & White Conspicuity tape Folding Side Step (RS)
	Cable Roller Centered at Front of Lower Deck	3 LED marker lights each side including mid turn
		Strobe light with toggle switch on rear

Models

Kalyn Hydraulic Sliding Axle Optional Equipment

☒ **2 Axle, 40 Ton, 50' Model**

☒ **Bolt on Side Step (Driver Side)**

Options

☒ **6 Function Wireless Remote**

☒ **Aluminum Wheels Outside all Axles**

☒ **OEM 235/75 R 17.5 16PR Tires**

☒ **AirWeigh Load Scale**

☒ **Tire Inflation**

☒ **Central Lube - 18 Point Manual**

Estimated Weight of the Equipment with the options :

18,350 lbs.

± 3% For trailers other than standard specification, weight and dimensional drawing will be provided by plant after order is received and accepted.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.