

Item HYDRAULIC DETACHABLE GOOSENECK Description Model: RTN60ETD3-PS TRAI		Model: RTN60ETD3-PS TRAILER
TONS CAPACITY	60 TONS IN ANY 16'	
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL	
CUSTOM/PAVER SPECIAL	TAPERED FRONT BEAMS (8-3/8" DEEP)	
PLATFORM WIDTH	8'-6"	
PLATFORM LENGTH	24' (HOLD 53' OAL) NOT TO EXCEED 43'-0" FROM THE 84" KINGPIN TO THE CENTER OF THE 2ND AXLE	
PLATFORM HEIGHT/ROAD CLEARANCE	22"/6" LOADED (ADJUSTABLE)	
CROSSMEMBER SPACING	ON 20" CENTERS	
AUXILIARY CROSSMEMBERS	OUTSIDE OF MAINBEAMS BETWEEN CROSSMEMBERS ON 10" CENTERS	
FRONT FOLDING RAMPS	41" LONG-WOOD FILLED-ADJUSTABI	LE
FRAME REINFORCEMENT	FOR 4 CLOSED COUPLE AXLES ONLY	
BUCKET TROUGH	40" FORWARD OF SLOPE AND CLEAR THROUGH THE 1ST AXLE	
BUCKET TROUGH FILLER	REMOVABLE, WOOD FILLED	
HYDRAULIC SYSTEM	FROM TRACTOR WETLINE	
GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT	
GOOSENECK SUPPORT CYLINDER	HYDRAULIC	
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/ VERTICAL A	AIR LOCK PIN
SWING CLEARANCE	108" & 84"	
FIFTH WHEEL HEIGHT (50" LOADED)	48"-50"-52"-54"-56" LOADED (ADJUST	ABLE)
1/8" ALUMINUM TOP COVER	OVER GOOSENECK AREA	
AIR BRAKES	16.5" X 7" W/ AUTO SLACKS & OUTBO	DARD DRUMS
ANTI-LOCK BRAKES	NONE (TRAILER GVWR EXCEEDS 120,000#)	
SPRING BRAKES	ON 2ND AXLE	
AXLES	(3) 25,000# 3/4" WALL W/ 23,000# BRA	AKES AND LIMIT CHAINS
TIRES	(12) 275/70R22.5 (H)	
WHEELS	ACCURIDE EXTRA POLISHED OUTER	RS, STEEL DISC INNERS
SUSPENSION	AIR RIDE W/ 50" AXLE SPACING	
SUSPENSION	AIR LIFT 3RD AXLE ONLY	
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANI	UAL
RAISING AND LOWERING VALVE	AT REAR OF TRAILER	
LIGHTS	L.E.D. RUBBER SEALED SYSTEM	
BATTERY BACK-UP	AMBER STROBE LIGHTS ON BATTER	RY-BACK UP
3RD TAILLIGHT PACKAGE	AMBER L.E.D. STROBE WARNING LA	MPS
LASH RINGS	(18) TOTAL- 6-PER SIDE (BENT STYL DECK FLAT STYLE ON 45 DEGREE A (FLAT STYLE)	
EXTENSION BRACKETS (OUTIGGERS)	12" SWINGING/REMOVABLE OUTRIG INCLUDES 12" DOUBLE HOOK-ON OU "FULL LENGTH" OF DECK	
DECKING	1-1/2" APITONG FULL WIDTH	

PAINT	GLOSS BLACK (2-PART URETHANE) STEEL PARTS TO MATCH PAINT COLOR
FLAG HOLDER SLOTS	IN BOLSTERS
REAR DECK	OPEN BOOMWELL WITH EXTRA LOW FIRST CROSSMEMBER AND WITH 1 1/2" APITONG OVER TIRES ONLY (BOLT-IN COVER PLATE)
REAR DECK	REMOVABLE WOOD FILLED BOOMWELL FILLER
REAR SLOPE (MAIN TO REAR DECK)	3 TO 1 (18 DEGREE) W/ OPEN CENTER
REAR SLOPE (MAIN TO REAR DECK)	REMOVABLE WOOD FILLED REAR SLOPE FILLER
ROLLER STOP AT REAR	4" HIGH, WIDTH OF MAIN BEAMS
FLAG HOLDER W/ THUMB SCREWS	1-PAIR FRONT CORNER OF DECK, 1-PAIR ENDS OF LIGHT PANEL
AIR AND ELECTRICAL CONNECTIONS	FOR FUTURE FLIP/REMOVABLE AXLE
ALUMINUM STORAGE BASKET BOLT-IN	(1) AT FRONT OF DECK