

HALE

TRAILER

BRAKE & WHEEL



A029657-A029666

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

XL SPECIALIZED TRAILERS

XL 130 Hydraulic Detachable Extendable

OVERALL LENGTH	59' 10"
OVERALL WIDTH	120"
CAPACITY	130,000 LB DISTRIBUTED; 130,000 LB IN 10' CLOSED 55,000 LB IN 5' FRONT AND REAR OF DECK FULLY EXTENDED - 110,000 LB TOTAL
WEIGHT +/- 3%	0,000 LB
GOOSENECK	
NECK STYLE	CLASSIC NECK
LENGTH	12' 5"
KINGPIN SETTING	16"
SWING CLEARANCE	105"
5TH WHEEL HEIGHT	49" W/ (7) VARIABLE RIDE HEIGHT POSITIONS
HYDRAULICS	13 HP HONDA UNIT SET UP WITH DUAL HYDRAULICS, STEEL LID
FLIP NECK	PREP FOR 72" FLIP NECK 72" FLIP NECK MAX KING PIN LOAD 105,000 LBS
MAIN DECK	
	10' WIDE OPEN FROM THE FRONT
LENGTH	31' 5" / OPENING TO 55' APPROX
LOADED DECK HEIGHT	18" W/ 4" GROUND CLEARANCE
DECKING	COVER CENTER OF TRAILER (OVER TRACKING CHANNEL) WITH 1 1/8" APITONG DECKING, FLUSH
CROSSMEMBER	FORMED CROSSMEMBERS ON 24" CENTERS
BEAMS	(4) 14" FAB I-BEAMS
D-RINGS	(14) BENT D-RINGS PER SIDE
D-RINGS	(9) BENT D-RINGS PER SIDE ON THE INSIDE
OUTRIGGERS	REMOVABLE SWING OUT OUTRIGGER BRACKETS ONLY ON 24" CENTERS DOUBLE FRONT OUTRIGGER
REAR DECK	
LENGTH	16'
LOADED DECK HEIGHT	45"
AXLES	(3) 25,000 LBS. NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	60"
ABS	N/A SPRING BRAKES ON (1) AXLE
TIRES	295 / 75R / 22.5 (G)
WHEELS	8.25 X 22.5 10-HOLE PILOT MOUNT STEEL DISC
BRAKES	16 1/2" X 7"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH (3) TAIL LIGHT ALUMINUM PACKAGE 4" AMBER STROBE TO BE USED AS 3RD TAIL LIGHT
DECKING	OPEN WHEELS BOLSTER STYLE, OPEN BOOM TROUGH COVERED BOOM TROUGH (BOTTOM PLATE ONLY) ALL PLATES 1/2" THICK 1/8" ALUMINUM TREAD PLATE BOLTED ON TOP OF EACH BOLSTER
CHAIN DROPS	(2) CHAIN DROPS PER FULL WIDTH BOLSTER
D-RINGS	(1) PAIR FLAT D-RINGS ON MAIN BEAMS AT FRONT (1) PAIR FLAT D-RINGS ON MAIN BEAMS AT REAR (2) PAIR FLAT D-RINGS IN BOOM TROUGH BENT D-RING OUTSIDE ON EACH FULL BOLSTER
STAKE POCKETS	(2) STAKE POCKETS AT REAR

PAINT

BLACK

ADDITIONAL

(2) PAIR OF FLAG HOLDERS
RAISE AND LOWER VALVE
PREP FOR A TWO AXLE BOOSTER
TOP LUGS FOR FLIP AXLE WITH LIFT AXLE
MANUAL RIDE HEIGHT CONTROL

EXTENSION STOPS ON 24" CENTERS
DELETE 31" FRONT FLIP RAMP
BUMP RAMP (EXTENDS 6" TAPER TO 4")
H.D.EXPANDED METAL TOOL BOX BETWEEN LOCKS AND BUCKET WELL PLATE
ON BOTH SIDES OF THE EXTENDED TRACK

(2) ADDITIONAL CLEARANCE LIGHTS PER SIDE ON MAIN DECK
DETACHABLE WHEEL AREA WITH MANUAL HORIZONTAL LOCK PINS
LIQUID FILLED GAUGE
REINFORCE OVERLAP BETWEEN FEMALE AND MALE BEAMS
(4) SPARE TIRE CARRIERS ON GOOSENECK (2) EACH SIDE
BUCKET WELL, 1/2" STEEL PLATE, REAR CENTER OF FEMALE DECK (APPROX 6' LONG)
(8) FLAT D-RINGS. (ONE EACH CORNER AND TWO BETWEEN EACH CORNER)
GREASE IN LIEU OF OIL IN AXLES
AIR LIFT ON 3RD AXLE
1/2" LOCKABLE LID AT REAR OF FEMALE DECK COVERING THE AIR AND ELECTRICAL
1/2" LOCKABLE LID AT FRONT OF WHEEL AREA COVERING THE AIR AND ELECTRICAL
BLACK DURABAK ANTI-SKID COATING ON MALE AND FEMALE TOP FLANGES
130,000 IN 10' CLOSED RATING
TO FIT TO: 22 FA 25343

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.