

HALE

TRAILER

BRAKE & WHEEL



A029678-A029702
VIN: 507201-507225

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

GVWR

GVWR:	Trailer to meet 68,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
Product Type:	HT Composite-XT
Composite New Design:	Composite

GEOMETRY

Length - Exterior:	53' -0"
** Length - Interior:	52' -6"
Width - Exterior:	102.36"
** Width - Interior:	101.5" Panel to Panel
Height - Exterior:	13' -6"
Height - Interior:	110" Nominal
Deck Height:	Standard application
Fifth Wheel Height:	47"
King Pin Location:	36"
Landing Gear Location:	107" from King Pin (+ 1"/-1/4")

TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL21(G), Low Rolling Resistance Tire
Tire Size:	295/75R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
Wheel Finish for Steel:	Powder Coated White Steel Disc
Tire Stem Valve Position:	Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
Valve Stem & Cap:	Myers TR-572-F19 Valve stem

UPPER COUPLER

* Approach Plate:	1/4" thick 80,000 Lb Yield - 6 Support Channels
King Pin (BTM Main) Plate:	1/4" thick 80,000 Lb Yield
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin
Front Bottom Rail:	Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle
Upper Coupler Tube Qt'y:	(1) Tubing Application - Joggled

BODY/BASE

* Forward Crossmember:	Steel Hat Shaped Upper Coupler to Landing Gear : 10" C/L
* Landing Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 9" C/L (6" On Forward Edge : 7ea)
* Bay Area Crossmember:	4" Steel I-Beams (80,000 PSI) : 8" C/L
* Running Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 8" C/L
Slider Body Rail (VT):	208" Rail Length
Slider Rail Supplier:	Hutchens Slider Rails

FLOOR

Upper Coupler Type:	3.40" Joggled with Exposed Coupler Top Plate (New STD)
Floor Specification:	1.38" (1-3/8") Nominal Domestic Laminated Oak Hardwood

* Floor Ratings - VT:	22,000 lbs Rated Floor per TTMA
Floor- Assembly Method:	Wood Floor Assembly
Floor Screws:	(3) 0.31" Dia. screws per Board on I beams
Threshold-Finish:	Hot Dip Galvanized
Threshold Plate:	0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts
Threshold-Application:	Standard Application

FRONT

Front Corner Radius:	4" Extruded Aluminum
Front Panel & Color - Dry:	0.05" Aluminum Prepainted White w/ natural color rivets
Front Corner Mat'l - Dry:	Extruded Aluminum
Front Posts:	(4) 2.5" Deep (16Ga) Steel Hats - Non AAR
Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid
Front Receptacle(7-Way):	Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug
Options - Front Receptacle(7-Way):	Phillips QCS Plug connector
Gladhand/7-Way Location:	(Interior Harness Routing) Overlaid on Lower Roadside Front)

SIDE

* Composite Side Material:	LX 2nd generation (G2) 6.5mm thick (0.4 outer/inner skin) Composite Panel, Pre-painted White, Both Sides, with natural color rivets
Side Posts:	14 Gauge Galv Steel 'A' Slotted Logistic Insets with Composite Panel color matching Outer Closure (For Composite New STD)
* Side Post Centers:	24" C/L Stiffener (Side Closure) - For Composite
Side Top Rail:	Side Top Rail for Composite (New STD)
Side Bottom Rail:	Side Bottom Rail for Composite XT (One Piece Extended Bottom Rail)
Fasteners to Bottom Rail:	Standard Rivets to attach C/Members to the Side Bottom Rail

REAR

Rear Frame:	Swing Door, 2.5" New Door Header Standard Trailers (with 1 Lock Rod Per LH & RH Door)
Rear Door Opening Spec.:	Standard Application
Floor Level:	Door to be Flush with Floor (STD)
Door Type for Dry Van - SW:	0.5" Composite Swing Door. Galvanized Prepainted White Interior & Exterior Skin
* Option - Door (Main Line):	Install Equal spring load door hold back No.2449-A CLEVELAND (= Fleet Engineering #023-00024)
Option - Door Install Instruct:	Standard Door Installation per Manufacturer's Recommendation
Option - Door & Hardware:	One(1) Rubber Door Bumper (1.25" Deep) on Hinge of each Swing Door
* Door Holder Type for Swing Door:	Additional Process for CLEVELAND Door Hold Back Main Line Installation
Hinges:	Four (4) Aluminum Hinges per Door (3" Height)
* Additional Hinge Option:	Additional One(1) Aluminum Hinge (Total 5 Per Door)
* Additional Lock Rod Option:	Additional Lock Rod - 1 Curbside & 1 Roadside
* Rear Underride Guard:	4" Tube Bolt on Assembly w/ Welded Perforated(Poached) Horizontal. Rear Impact Guard (RIG30-NEW)
Option - Horiz Member/Other:	One piece roll formed w/continuous welding
Underide Bolt Spec.:	Geomet bolts & nuts - Standard
* Step & Under Ride Accessories Option:	Welded Step-Intermediate Step with Perforated material Centered between Rear Impact Vertical Members
* Dock Bumper:	Pair 3 X 5.88 HT High Performance Polyurethane Radius Bumper ATRO Black Color
Rubber Bumper Location:	Inboard of Light Protector Bars (Standard)
* Rear Corner Post Grab Handle:	(1)Grab Handle-Low Profile, Chrome Steel Installed to Roadside Exterior Rear Door w/36" Long & Thru Bolted (Bolting Type)
* Rear Frame Design:	Rear Frame Enclosed Door Sill Design

LIFT GATE

ROOF

Roof Panel:	0.040" Aluminum
Roof Bow:	16 Gauge Galvanized Steel Anti-Snag
Roof Bow Centers:	24" Centers Full Length

LANDING/SCUFF

- * Front Lining: 0.50" Ponderosa Plywood Mounted to Front Posts Full Height
- * Ceiling (Roof) Lining: 0.25" Ponderosa Plywood, Full Length & Full Width
- Base Side Scuff: 16" High Integral Alum Composite XT (Extended Bottom Rail - Integral Scuff Band) - Composite XT STD without Additional scuff
- * Front Scuff: 0.63" x 12" High Black Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)

LANDING GEAR

- L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG
- L/Gear Mt'g Method: Inboard Mounting (Standard)
- L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile
- L/Gear Ground Clearance: Nom. 12" Ground Clearance
- * L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate with "Flying H" Hyundai Logo (Per customer request)
- L/Gear Crank Handle: Roadside
- L/Gear Options: None (HT STD)
- L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

RUNNING GEAR

- Bogie Type: Sliding Tandem(2) Axle Bogie
- Axle Spacing: 49" Axle Spacing
- Axle ABS System: Tandem Axle w/2S1M ABS System
- Bogie & Axle Location: Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
- Option-Related Bogie Stopper Feature: STD plug stopper
- Susp. Manufacturer: Hendrickson
- Suspension Capacity: Standard Duty
- * Hendrickson Susp. Specification: Hendrickson Ultraa-K Air Ride
- Surelok (Anti-Dock): Surelok (Anti-Dock) Installed
- Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw
- Susp. Sub-Frame: Hendrickson K-2 STD Duty (Vantraxx, Intraxx)
- Type of Susp Spring: Air Bag
- Spring Specification: Air Bag
- Axle Diameter: 5.75"
- Axle Supplier: Hendrickson
- Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
- Axle-Track Length: 77-1/2"
- * Axle-Spindle Type: Parallel Spindle
- Brake Lining Size: 16.5" X 7" Drum Brakes
- Brake Lining Spec.: Hendrickson Extended Service H20
- Brake Control System: 2S/1M Wabco iABS
- Spring Brake Control: Sealco 110500 Springbrake Priority
- Brake Cont-Hose & etc.: Standard Air Line & Hose Application (US&Canada)
- * Slack Adjuster Spec.: Wabco Auto-5.5", 28 Spline EasyFit (No Grease)
- * Brake Chamber Spec.: Wabco Premium Chamber
- * Stroke Length: 3" Long Stroke Length
- * Hub Specification: Conmet 10 Stud Hub Piloted Outboard Iron Hub with Casting 10083939, Parallel Spindle
- Drum Specification: Conmet Cast Drum
- Hub/Drum-Opt(Nut&Other): Standard
- Bearing Specification: Stemco
- Lubrication Spec.: Chev Delo Gear EP5 80-90 oil
- Wheel Seals Spec.: Stemco Platinum Performance Plus, Discover Seals, Sentinel Hub Cap, Pro-Torq Nut
- * Hubodometer: Stemco Hubodometer, Bracket Mounted, Reading in Miles
- * Hubodometer Location: Curbside (RH) Front Axle
- Tire Inflation Pressure: 100 PSI
- * Air Tank Vendor: Sanborn Steel Air Tank

ELECTRICAL

* Harness-General Spec.:	Molded Color Code Phillips Harness with QCS Plug
Harness-Special Feature:	Manufacturer's Standard Feature
* Front Light:	(2) Trucklite 33275Y LED PC Rated Mounted with Grommet
* Rear ID Header Light:	(5) Trucklite Dual Function 33204R LED (Cluster of 3 & 1 Each Outboard)
* Rear ID-Special Feature:	Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop functionality, 2 Lamps outboard with Marker & Turn functionality
Rear Side Marker Type(Shape):	Mini Button Style Lamp with Antitheft Bracket
* Rear Side Marker Detail Spec:	(2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware
Rear Side Marker MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
S/T/Tail Light-Quantity & Type:	(4) Trucklite 40 or 44 Series (Round Style) or Equivalent
* S/T/Tail Light-Detail Spec:	(4) Trucklite 44331R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets
Main Mid-Turn Light:	Install the Mid turn lamp
Mid-Turn Mounting Method:	Mounting Bracket
* Main Mid-Turn Light-Detail Spec:	(2) Trucklite 60272Y LED Gray Flange Mounted with Stainless Steel Rivets & Anti-theft brackets
* ABS Light Detail Spec:	(1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
ABS Light MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
* License Light:	(1) Trucklite 33210C LED with 33815 Anti-Theft Flange
Option Related Harness/Wiring:	Standard
Electrical Related Regulation:	Standard Application

MARKING/DECALS

HT & Product Type Decal Package:	Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)
Decal Package:	Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Decal Opt 2-Decal Location:	Standard Application
Decal Opt 3-Decal Installation:	Standard Application
Conspicuity Vendor:	3M
Conspicuity Markings:	Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate:	Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install:	Standard Install Location - Roadside Below Door Sill
Furnish Document Holder:	Factory Furnished
Document Holder Detail Spec:	(1) Phillips 16-802
* Document Holder/Manifest Loc.:	Overlaid on Lower R/S Front. 18" from the bottom of the front sheet between the front post & corner radius on the roadside

PAINT/FINISH

Upper Coupler Finish:	Galvanized-Whole upper coupler section
Crossmembers Finish:	HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)
Axle & Components Finish:	Black Undercoating
Susp. Sub-Frame Finish:	Black Undercoating
L/Gear(K-Bracing) Finish:	Hot Dip Galvanized
L/Gear(Upper Leg) Finish:	Hot Dip Galvanized
Rear Frame-Finish:	Hot Dip Galvanized
Rear Frame-Paint Color:	None (For Galvanized or Stainless Steel)
Rear Underride-Finish & Spec.:	Hot Dip Galvanized & Welded Horizontal Member
Rear Underride-Paint Color:	None (For Galvanized or Stainless Steel)

MISCELLANEOUS

Mudflap Provider:	Factory Furnished Mudflaps
Mudflap Specification:	24"x30" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Location:	Suspension frame (Tandem/Single axle frame without P.H.)
* Mudflap Mounting Method/Install:	Mounted on Ultraa-K Susp. w/ H.D Washer Retainer
Mudflap Bracket design:	1 Piece Bracket

- * Lift Pad Spec.: Install HT Occasional use lift pads for delivery
- * Import export Decals: With HYUZ Decals

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.