	SALES	RENTALS	PARTS	SERVICE
	Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
	Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
TRAILER	Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
BRAKE & WHEEL	Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
	Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
A029761-A029763	Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
AUZ9701-AUZ970J	Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310
VIN: 44930-44932 haletrailer.com @haletrailer f 🕑 📼 💿				
	800-232	2-6535 *F	FINANCING	AVAILABLE

BASE MODEL DC-17.5	Drop Deck Combo Flatbed
components	description
CAPACITY	Standard Beam Pkg - 80,000 GVWR (54,000 in 4' Span)
OVERALL LENGTH	53' - Base Weight 11,420#
TOP DECK-LGTH/HGT	10'6" Length = 59" Height
LOWER DECK-LGTH/HGT	42' 6" Length = Front 36.50", Center 37.50" Rear 35.50" Heights
OVERALL WIDTH	8' 6"
KING PIN SETTING	24" - Tapered Pickup Plate
UPPER COUPLER PLATE	1/4"
UPPER COUPLER PLATE	48"
FRONT SKIRT	Aluminum Front and Corners
REAR SKIRT	Aluminum
BULKHEAD	
MAIN FRAME	26" PreCamb Beams-130K Tru-Strength Flanges - Limited Lifetime Warranty
SIDE RAILS	6"-Alum-Extruded W/Double L Track
TOP DECK FLOOR SILLS	4" Steel I-Beam - 18" O.C.
	4" Steel I-Beam 12" O.C. HD Pkg
COIL HAUL PACKAGE	Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer
FLOOR DECKING	1-1/8" HD Aluminum W/4 Nailer Boards - * * * Old Style Flooring * * *
WINCHES	12 DOUBLE L
WINCH TRACK	Double L Aluminum - Extruded Siderail C/S & R/S - Both Sides
TIE BAR	D/S & C/S - Full Length Both Sides - 3/8" x 2"
STRAPS	None
LANDING GEAR	Two Speed - Jost A500
SUSPENSIONS	Cush - Air Ride - 23K - RAS - Rear Axle Slider
SUSPENSION LOCATION	R.A.S Cal Legal (Center of KP to Center of Rear Axle 40' in Closed Position)
AXLES	(2) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - 17.5 Tires
AXLE SPACING	RAS - 2 Position - 61" & 10' 2" Spread
LIFT AXLE	None
DUMP VALVE	ElectWired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#)
SCALES	None
PARKING BRAKES	All Axles
ABS SYSTEM	Wabco ABS System 2S/1M
DUST SHEILDS	None
WHEELS	Disc - Hub Piloted - 17.5 (2-AX) - Steel
TIRES	235/75R 17.5 - Double Coin
TIRE INFLATION SYSTEM	Tire Maax PRO-2 Axle 235 or 245/70r17.5-125 P.S.I Part #
ANTI-SAIL MUD FLAPS	Behind Rear Axle
STAKE POCKETS	24" O.C. Sides & 5 Across Rear
SPOOL	Triangular Shaped
RUB BAND ALUM	3/8" x 3" - Aluminum - Recessed for DOT Tape
DOCK BUMPERS	Rubber Inboard
CARGO TIE DOWN	14 Pair of Recessed Chain Ties Evenly Spaced
	• •
CONTAINER TWIST LOCKS	None
DUNNAGE RACK	Tire Carrier Positioned In Front of Main Beams Between Landing Gear
	None
	None
	None
	Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS	
PAINT	Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted
DECAL PACKAGE	Standard Dorsey Logo Kit
CUSTOM 1.	None
CUSTOM 2.	None
CUSTOM 3.	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.