



A029886-A029897 **FONTAINE** TEMP VIN: S028791-S028802

SALES | RENTALS | PARTS I SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord. NC: Raleigh, NC 800-438-2250 833-418-9777 Delmar, DE: 800-569-1400 866-486-1400 Scranton, PA: Des Moines, IA: Springfield, MA: 800-854-5306 888-673-5011 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235

haletrailer.com | @haletrailer (f) in (© **800-232-6535** *FINANCING AVAILABLE

800-828-3055

Walpole, MA:

800-854-5310

Velocity Drop Deck 48' Closed Air (Model Code: HAVSD12CTA)

Jacksonville, FL:

Length / Width: 48 feet x 102 inches

Suspension Type: Air tandem

Deck Lengths: 10 feet front and 38 feet rear

Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Rear Deck Height: 40 inches - loaded

Flooring: 1 1/8 inch wood

Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

Side Rails: 6 inch structural channel @ 6.5 lbs/ft Stake Pockets: 3/16 inch steel on 24 inch centers **Pipe Spools:** Double between stake pockets

Rubrail: 3/8 inch x 2 1/2 inch steel Main Beams: 130K load bearing flanges

Kingpin: 18 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM standard

Knee Braces: Fabricated on approx. 60 inch C/C Bulkheads: Removable aluminum bulkhead - no turnback - 48 inches high

Bulkhead Pockets: 4 - F-5 DOT-type steel

Number of Axles: 2 Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed ABS: Meritor Wabco iABS 4S/2M - no cable or tool

Axle Spread: 49 inches - set at rear

Hub and Drums: 10-hole hub-piloted with outboard cast drums Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ** Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 255/70R 22.5 16PR OEM standard Tire Inflation System: None standard Suspension Detail: AANL23K Intraax air ride

Auto Glad Hand Dump: Installed

Front Corners: Tapered

Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD

Paint: Black urethane with Velocity decals - STANDARD Conspicuity Tape: Per NHTSA specs - installed on rubrails Bumper: Weld-on type - meets underride requirements Mudflaps: 1 set OEM standard behind rear axle

Winch Track: Steel on road side: 8-foot front deck and full length on rear deck where possible

Sliding Winches: 12 ZINC: 2 front deck and 10 rear deck

27 foot Winch Straps: None standard 30 foot Winch Straps: None standard Dock Bumpers: 1 pair rubber on rear

Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate Unit Numbers & Decals: Not installed

