

HALE TRAILER BRAKE & WHEEL



A029916-A029921
TEMP VIN: S028820-S028825

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Infinity Low Deck Height Drop Deck 53' Rear Axle Slide Air (Model Code: HAILD22RSA)

Length / Width: 53 feet x 102 inches
Suspension Type: Rear axle slide
Deck Lengths: 11 feet front and 42 feet rear
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
Rear Deck Height: 36 inches - loaded, 37 inches unloaded
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips
Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel
Single Coil Hauling Package: Included
Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
Chain Cargo Tie Downs: 17 pair recessed in siderails
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
Rubrail: Integrated with siderail
Main Beams: 130K load bearing flanges
Kingpin: 30 inches
Fifth Wheel Height: 49 inches
Landing Gear: OEM standard
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front
Bulkheads: None standard
Number of Axles: 2
Axle Spindle: Tapered
Brakes: 12 1/4" X 7 1/2"; Spring brakes; auto slacks; Linings for 20,000# GAWR
Air Line Filters: (2) Meritor In-line type installed
ABS: Meritor Wabco iABS 4S/2M - no cable or tool
Axle Spread: 122 inches open - 61 inches closed: Meets California, Canadian RTAC and BC dimensional specifications in closed position
Hub and Drums: 8-hole hub-piloted with outboard cast drums
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 17.5 x 6.75 4 steel disc inside wheels - 4 outside aluminum Lvl. One Buffed with 4 Spacers
Tires: 245/70R 17.5 18PR OEM premium (20,000# GAWR)
Tire Inflation System: Hendrickson TIREMAAX PRO inflation system
Suspension Detail: Hendrickson HT250US and HTZUS air ride
Air Assist Slide Box Pins: Standard mount of controls on slider frame
Auto Glad Hand Dump : Installed
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle
Front Corners: Tapered
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD
Paint: Black urethane on steel parts with Infinity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails and rear bumper
Bumper: Weld-on type - meets underide requirements - painted steel
Mudflaps: 1 set OEM standard behind rear axle only
Winch Track: Full length integrated double L type aluminum on both sides where possible -- STANDARD
Sliding Winches: (15) ZINC: 8 Road Side - 7 Curb Side with Sliding Rope Hook/Winch Strap Hook Retainers
27 foot Winch Straps: None standard
30 foot Winch Straps: None standard
Dock Bumpers: 1 pair rubber on rear
Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop
Hubodometer: None standard
Registration Holder: Install registration holder - OEM standard
Tool Box: 1 aluminum double door box - 18 inches x 18 inches x 60 inches - installed Road Side
VIN Plate: Bilingual US/Canadian VIN plate
Unit Numbers & Decals: Not installed
Fontaine Select to Remove (2) Inner Tail Lights of 3 Light Rear & Install (2) Amber Strobe Lights Controlled by Manual Toggle Switch on Rear (*NOTE: Customer Must Plug Together)
Fontaine Select to Install (6) Extra Pair Side MARKER LIGHTS spaced between existing lights (*Total 9 Lights Ea. Side)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.