

# HALE

## TRAILER

### BRAKE & WHEEL



A030361-A030380  
VIN: 90608-90627

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

#### Alum Frameless Half RND

**Weight** 9862 lbs. \*\*\* **Cubic Yards** 49

#### BODY

LOAD PROFILE	MATERIAL, 80K GVWR
LENGTH	38 FT. (34 FT. 7 IN. FLOOR)
WIDTH	96 WIDE BODY, 102 WIDE AXLES
BODY STYLE	RADIUS BULKHEAD LOW PROFILE
FLOOR LINER	NONE
VIBRATOR	NONE
RUBBER SEAL	YES
AIR FAIRINGS	NONE
WALL HEIGHT	64
HOIST	8-5-250 - CUSTOM
BULKHEAD LADDER	BULKHEAD DOOR W/ GRAB HANDLE & STEP 3/16 IN. BULKHEAD
SHOVEL HANGER	YES, CURB SIDE
FRONT FENDERS WITH FLAPS	NONE
ALUMINUM ROLL CAP	8 IN. RISE ROLL
REAR ROLL CAP	YES, 8 IN. RISE ROLL
FLOOR / SIDES	1/4 IN. FLOOR, 1/4 IN. SIDES
LAST 8 FT 3/16" OVERLAY	
SIDE STEPS / LADDER	LADDER OUTSIDE D.S.
BULKHEAD LINER	NONE
TIRE CARRIER	NONE
REAR POCKET WIND DEFLECTORS	NONE

#### LIGHTS

LIGHT TYPE	GROTE L.E.D. W/ GROMMET
LIGHT PANEL	3 LARGE-3 SMALL-3 LARGE
APRON	1/4 IN. X 6 IN. LIGHT APRON
STD. MARKER LIGHTS	(5) EACH SIDE
MID-TURNS	(1) PAIR L.E.D. (NON-COMBO)
BACK-UP LIGHTS	(1) PAIR L.E.D. BACK-UP LIGHTS
AUXILIARY CABLE	7 WAY (ISO)
BACK-UP LIGHT WIRE	AUXILIARY (BLACK WIRE)
REAR POCKET LIGHTS	1 PAIR

#### GATE

GATE SHEET THICKNESS	3/16 IN. SHEET & POST
GATE OPERATION	BALL VALVE
MANUAL CONTROL	
HINGE TYPE	O. S. SWING D.S. W/ INPOCKET GROUND CONTROL
COAL DOOR	NONE
CHUTE	NONE
SPREADER CHAINS	NONE

WINDERS / SAFETY LATCH	WINDERS (1) EACH SIDE AND (2) BOTTOM
TARP HOOKS	NONE
GATE LINER	NONE

## PRIMARY AXLES

MODEL	CLOSED TANDEM
NO. OF PRIMARY AXLES	2
SUSPENSION	HEND. INTRAAX AAT-25K W/ HXL-5
	USE AAT30K SUSPENSIONS
AXLE SPACING	52
	add restraining straps to front axle shocks
AXLES	AXLE FOR INTRAAX ONLY
BRAKES	7 IN. XL, W/ 30-30 CHAMBERS
CAM GUARDS	HEND. INTRAAX
HUB AND DRUM	CENT W/ DURALITE HUB HP OB 10 STUD TP, LS, 7 IN.
TIRES	GENERAL RA 11 R 22.5 16 PLY
WHEELS	ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP)
	INSULATORS BETWEEN THE ALUMINUM WHEELS.
PRIMARY AXLE TIRE INFLATION SYSTEM	HENDRICKSON SYSTEM (TIREMAAX PRO)

## LIFT AXLES

NO. OF LIFT AXLES	0
LIFT AXLE SUSPENSION	NONE
LIFT KIT	NONE
LIFT AXLE	NONE
LIFT AXLE BRAKES	NONE
LIFT AXLE CAM GUARDS	NONE
LIFT AXLE HUB AND DRUM	NONE
LIFT AXLE TIRES	NONE
LIFT AXLE WHEELS	NONE
LIFT AXLE CONTROLS	NONE
FREE WHEEL VALVE	NONE
LIFT AXLE TIRE INFLATION SYSTEM	NONE

## CHASSIS

5TH WHEEL PLATE	BREAK-AWAY PIN @ 49 IN.
GALVANIZED SUSPENSION HANGERS	YES
SUSPENSION CONTROL	AUTOMATIC DUMP W/ PARKING BRAKE
ABS FOR TRAILER	(1) 4S2M MERITOR / WABCO
SLACKS	AUTOMATIC
AXLE LUBRICATION	HXL, SYNTHETIC SEMI-FLUID GREASE
HUBODOMETER	22.5, TP, BOLT-ON STEMCO MILES
	DRIVER SIDE FRONT AXLE
DUST COVERS	NONE
DOLLIES - LANDING GEAR - LANDING LEGS	JOST A450 - (62,500 lb.) - 10 YEAR NO LUBE - STEEL - D.S.
DOLLIE REINFORCEMENT	HEAVY DUTY (DROP & LOAD APPLICATION)
REGISTRATION HOLDER	TUBE TYPE HOLDER
AIR GAUGE / SYSTEM	YES, IN FRONT
ENCLOSURE FOR SWITCHES	STAINLESS STEEL
	TAILGATE, SUSPENSION DUMP
AIR TANKS	ALUMINUM TANK
HYDRAULIC HOSE FITTING	1 IN. X 120 IN. HOSE W/ WING FITTING
FLAPS FRONT OF TIRES	FLAP IN FRONT OF FRONT AXLE
FLAPS REAR OF TIRES	FULL RUBBER ACROSS REAR OF TRAILER

## TARP

TARP MANUFACTURER	NONE
TARP CONFIGURATION	NONE
TARP CONTROL	NONE
TARP COLOR	NONE
BOW HOLDERS	NONE

TARP BRACKET	NONE
MOTOR	NONE

PAINT	
HANGERS	GALVANIZED
SUSPENSION COLOR	BLACK SOFT COAT
DOLLIES	BLACK (931716)
HOIST COLOR	BLACK (931716)
5TH WHEEL PLATE COLOR	BLACK (931716)
PIN STRIPING	BLACK (931716)
MAC LOGOS	BLACK (930248)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.