



A030502-A030506 VIN: S029398-S029402

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f 쭞 🛅 🎯 🛗

**800-232-6535** \*FINANCING AVAILABLE

## FRAMELESS MVP SS

| Model # TNAR39NF600      | Weight | <b>11013</b> lbs.                  | ***       | <b>Cubic Yards</b>    | 55        | VIN# 5MADN392XTH085114 |
|--------------------------|--------|------------------------------------|-----------|-----------------------|-----------|------------------------|
| BODY                     |        |                                    |           |                       |           |                        |
| LOAD PROFILE             | N      | //ATERIAL, 80K GV\                 | ΝR        |                       |           |                        |
| LENGTH                   | 3      | 39                                 |           |                       |           |                        |
| WIDTH                    | ç      | 96                                 |           |                       |           |                        |
| FLOOR                    | 1      | /4 IN. W/ 3/8 IN. LA               | ST 10 FT  |                       |           |                        |
| CROSSMEMBER SPACING      | 1      | 2 IN.                              |           |                       |           |                        |
| SIDE PLACEMENT           | (      | DUTSET SMOOTH S                    | SIDE PAI  | NEL                   |           |                        |
| FLOOR LINER              | 1      | IONE                               |           |                       |           |                        |
| VIBRATOR                 | ١      | NONE                               |           |                       |           |                        |
| RUBBER SEAL              | )      | /ES                                |           |                       |           |                        |
| AIR FAIRINGS             | ١      | NONE                               |           |                       |           |                        |
| WALL HEIGHT              | 6      | 60                                 |           |                       |           |                        |
| WALL THICKNESS           |        | 57% STANDARD 1.5<br>PANELS175" WAL |           | S150" WALL & 33% - HE | EAVY 1.5" |                        |
| WALL LINER               | ١      | NONE                               |           |                       |           |                        |
| TOP RAIL OPTION          | 5      | SOLID                              |           |                       |           |                        |
| SOLID                    |        |                                    |           |                       |           |                        |
| REAR POCKET SLOPE        | 2      | 2.75                               |           |                       |           |                        |
| HOIST                    | 8      | 8-5-265 - CUSTOM                   |           |                       |           |                        |
| REMOTE GREASE            | F      | REMOTE HOIST GR                    | EASE      |                       |           |                        |
| BULKHEAD                 | 3      | 3/16 IN.                           |           |                       |           |                        |
| BULKHEAD TYPE            | F      | RADIUS CORNERS                     |           |                       |           |                        |
| BULKHEAD DOOR            | E      | BULKHEAD DOOR D                    | ).S. W/ C | GRAB HANDLE & STEP    |           |                        |
| BULKHEAD SLOPE PLATES    | ١      | IONE                               |           |                       |           |                        |
| LOWER BULKHEAD WRAP      | 1      | 10                                 |           |                       |           |                        |
| BULKHEAD STEPS           | ١      | NONE                               |           |                       |           |                        |
| SIDES STEPS D.S.         | L      | AST OUTSIDE ONL                    | _Y        |                       |           |                        |
| SIDES STEPS C.S.         | ١      | NONE                               |           |                       |           |                        |
| SHOVEL HANGER            | ١      | NONE                               |           |                       |           |                        |
| FRONT FENDERS WITH FLAPS | (      | CORNER W/ FLAPS                    |           |                       |           |                        |
| ALUMINUM ROLL CAP        | ١      | NONE                               |           |                       |           |                        |

| LIGHTS             |  |
|--------------------|--|
| LIGHT TYPE         | GROTE L.E.D. W/ GROMMET                                |
| LIGHT PANEL        | 3 LARGE-3 SMALL-3 LARGE (FULL LIGHT PANEL) OOO 000 OOO |
| APRON              | 3/8 IN. X 1-1/2 IN. FULL LIGHT SHIELD                  |
| STD. MARKER LIGHTS | (7) EACH SIDE  |
| MID-TURNS          | (1) PAIR L.E.D. (COMBO)                                |
| BACK-UP LIGHTS     | NONE   |
| AUXILIARY CABLE    | NONE   |
| BACK-UP LIGHT WIRE | NONE   |

| GATE                   |   |
|------------------------|---|
| GATE SHEET THICKNESS   | VERTICAL PANELS                             |
| GATE OPERATION         | AIR CAB CONTROL AND BALL VALVE              |
| HINGE TYPE             | O. S. SWING C.S. W/ INPOCKET GROUND CONTROL |
| COAL DOOR              | 14 IN. STAINLESS HANDLE                     |
| CHUTE                  | NONE  |
| DOUBLE HANDLE DOOR     | NONE  |
| GATE BRACING           | NO BRACING (SMOOTH SIDE PANELS)             |
| HALF ROUND ON GATE     | NONE  |
| ANGLE ON TOP OF GATE   | NONE  |
| SPREADER CHAINS        | NONE  |
| WINDERS / SAFETY LATCH | WINDERS (1) EACH SIDE                       |
| TARP HOOKS             | NONE  |
| GATE LINER             | NONE  |

| PRIMARY AXLES                         |  |
|---------------------------------------|--|
| MODEL                                 | TANDEM                                     |
| NO. OF PRIMARY AXLES                  | 2  |
| SUSPENSION                            | HEND. INTRAAX AAT-25K W/ HXL-5             |
| AXLE SPACING                          | 52   |
| SUB-FRAME                             | WIDE I-BEAM (17 IN.)                       |
| AXLES                                 | AXLE FOR INTRAAX ONLY                      |
| BRAKES                                | 7 IN. XL, W/ 30-30 CHAMBERS                |
| CAM GUARDS                            | HEND. INTRAAX                              |
| HUB AND DRUM                          | CAST W/ STEEL HUB HP 10 STUD TP, LS, 7 IN. |
| TIRES                                 | GENERAL RA 11R 24.5 16 PLY                 |
| WHEELS                                | ALUMINUM HP 24.5X8.25 - ALL POLISHED (XP)  |
| PRIMARY AXLE TIRE INFLATION SYSTEM    | NONE                                       |
| prep axles for Tiremaax CP inflations |  |

| LIFT AXLES                      |      |
|---------------------------------|------|
| NO. OF LIFT AXLES               | 0    |
| LIFT AXLE SUSPENSION            | NONE |
| LIFT KIT                        | NONE |
| LIFT AXLE DISTANCE              | N/A  |
| LIFT AXLE                       | NONE |
| LIFT AXLE BRAKES                | NONE |
| LIFT AXLE CAM GUARDS            | NONE |
| LIFT AXLE HUB AND DRUM          | NONE |
| LIFT AXLE TIRES                 | NONE |
| LIFT AXLE WHEELS                | NONE |
| LIFT AXLE CONTROLS              | NONE |
| FREE WHEEL VALVE                | NONE |
| LIFT AXLE TIRE INFLATION SYSTEM | NONE |

| STEERABLE LIFT AXLES         |      |
|------------------------------|------|
| NO. OF STEERABLE AXLES       | 0    |
| STEERABLE AXLE SUSPENSION    | NONE |
| STEERABLE AXLE DISTANCE      | N/A  |
| STEERABLE AXLES              | NONE |
| STEERABLE AXLE BRAKES        | NONE |
| STEERABLE AXLE HUB AND DRUMS | NONE |
| STEERABLE AXLE TIRES         | NONE |
| STEERABLE AXLE WHEELS        | NONE |
| STEERABLE AXLE CONTROLS      | NONE |
|                              |      |

| CHASSIS                |                |
|------------------------|----------------|
| PIN SETTING            | 16             |
| 5TH WHEEL PLATE        | BREAK-AWAY PIN |
| 5TH WHEEL PLATE HEIGHT | 49 IN. HIGH    |

| TANDEM DRIVE   |
|--|
| YES  |
| 3/8 ALUM   |
| AIR IN CAB & BALL VALVE                              |
| (1) 2S1M MERITOR / WABCO                             |
| AUTOMATIC  |
| HXL, SYNTHETIC SEMI-FLUID GREASE                     |
| NONE   |
| NONE   |
| NONE   |
| JOST AX-150 - (55,000 LB.) - 10 YEAR ALUMINUM - D.S. |
| NONE   |
| NONE   |
| NONE   |
| ALUMINUM TANK  |
| 1 IN. X 108 IN. HOSE W/ WING FITTING                 |
| FLAP IN FRONT OF FRONT AXLE                          |
| FULL RUBBER ACROSS REAR OF TRAILER                   |
| NONE   |
|  |

| TARP              |      |  |
|-------------------|------|--|
| TARP MANUFACTURER | NONE |  |
| TARP CONTROL      | NONE |  |
| TARP COLOR        | NONE |  |
| BOW HOLDERS       | NONE |  |
| TARP BRACKET      | NONE |  |

| GALVANIZED      |
|-----------------|
| BLACK SOFT COAT |
| BLACK (931716)  |
| NONE            |
|                 |

| ACCESSORIES                       |      |  |  |
|-----------------------------------|------|--|--|
| NO. OF CHAIN TIE DOWNS (PER PAIR) | NONE |  |  |
| (CUSTOMER MUST SPECIFY LOCATION)  |      |  |  |
| TOW MOTOR PACKAGE                 | NONE |  |  |
| COIL RACK ANGLES                  | NONE |  |  |
| LOAD LEVEL INDICATOR              | NONE |  |  |
| 3-1/2 IN. ANGLES UNDER RAIL       | NONE |  |  |
|                                   |      |  |  |