

HALE TRAILER BRAKE & WHEEL



A030628-A030702
TEMP VIN: S029518-S029592

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Velocity Drop Deck 48' Wide Spread Air (Model Code: HAVSD12WSA)

Overall Length: 48 feet x 102 inches (October - November)

Suspension Type: Wide spread air

Deck Lengths: 10 feet front and 38 feet rear

Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Rear Deck Height: 40 inches - loaded

Flooring: 1 1/8 inch wood

Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

Side Rails: 6 inch structural channel @ 6.5 lbs/ft

Stake Pockets: 3/16 inch steel on 24 inch centers

Pipe Spools: Double between stake pockets

Rubrail: 3/8 inch x 2 1/2 inch steel

Main Beams: 130K load bearing flanges

Kingpin: 18 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM standard

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkheads: Removable aluminum bulkhead - no turnback - 48 inches high

Bulkhead Pockets: 4 - F-5 DOT-type steel

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed

ABS: Meritor Wabco iABS 4S/2M - no cable or tool

Axle Spread: 122 inches - set at rear

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 255/70R 22.5 16PR OEM standard

Tire Inflation System: None standard

Suspension Detail: AANL23K Intraax air ride

Auto Glad Hand Dump: Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Air Lift: None Standard

Front Corners: Tapered

Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD

Paint: Black urethane with Velocity decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed on rubrails

Bumper: Weld-on type - meets underride requirements

Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle

Winch Track: Steel on road side: 8-foot front deck and full length on rear deck where possible

Sliding Winches: (12) ZINC Finish: 2 front deck and 10 rear deck

27 foot Winch Straps: None standard

30 foot Winch Straps: None standard

Dock Bumpers: 1 pair rubber on rear

Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.