



Hale Trailer Brake & Wheel

030772-030776

components	description
CAPACITY	45FT 2Axle GVWR 66,290LBS
OVERALL LENGTH	45'
OVERALL HEIGHT FRONT	13'-1"
OVERALL WIDTH	8' 6" - 45ft
UPPER COUPLER HEIGHT	48"
UPPER COUPLER PLATE	5/16" Plate
KING PIN SETTING	36"
SWING CLEARANCE	90"=36KP
LANDING GEAR	Two Speed-Holland Mark "V"
SUSPENSIONS	Spring Ride - Hutchens-2 Axle
SUSPENSION LOCATION	Set at Rear Most Position
AXLES	(2) 22,500K Capacity - Type 30 Chambers - Auto Slacks - ABS
AXLE SPACING	49"
LIFT AXLE	None
WHEELS	Disc - Steel - Hub Piloted- 22.5-(-56#)
TIRES	11R22.5-Manufacturer Choice
FRONT TYPE	10" Diagonal
FRONT MATERIAL	Aluminum .063 - Pre Painted White Aluminum
LADDERS	None
REAR DOOR TYPE	Heavy Duty Aluminum Top Hinged Chip Gate - Top Half Open for Blow In W/Wear Pads
REAR DOOR MATERIAL	Heavy Duty Galvanized Mesh
SIDE SHEET MATERIAL	.063 Aluminum Smooth(+140#)
SIDE POST	Extruded Aluminum on 16" Centers
SIDE SHEET COLOR	Pre Painted White
LOWER RAIL	Heavy Duty - Aluminum Lower Rail
SIDE VENTS	7 Per Side - 22" in Height and Framed - Expanded Metal Vent Screen for 16" Post Spacing
FRONT VENT	None
INSIDE LINING	Front - H.D. Aluminum Chip Sheild & 60"x30'.026 Galvanized Sht Top/Center
ROOF ASSY	.063 Alum Smooth Sheet W/ Exp. Bows 16/16/16 CTRS
FLOOR	Corr Fabricated Aluminum
FLOOR SILLS	4" Steel - Wax-Dipped I-Beam w/ Undercoating
LOAD BREAKERS	4 - 36" Aпитong-Staggered on Floor(Tippers Only)
SILL SPACING	12"/16"/12" STD
DUST SHIELDS	None
ANTI-SAIL MUD FLAPS	Behind Rear Axle
BUMPER	H.D. 3" x 4" Push Bumper
LIGHTS	Sealed Wiring Harness W/ LED PKG
CUSTOM LIGHTS	None
PAINT	Black -Fifth Wheel and Rear Frame
UNDERCOAT	Valspar - Black Corrosion Resistant
PICK UP EYE FRONT	None
CUSTOM 1	None
CUSTOM 2	None
CUSTOM 3	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.