



EAST GENESIS UNLOADER

OPEN TOP



A030811-A030814

VIN: 92174-92177

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894
Baltimore, MD: 888-601-7500
Concord, NC: 800-438-2250
Delmar, DE: 866-486-1400
Des Moines, IA: 888-673-5011
Elkton, MD: 800-544-7127
Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944
Portland, ME: 800-325-4253
Raleigh, NC: 833-418-9777
Scranton, PA: 800-569-1400
Springfield, MA: 800-854-5306
Voorhees, NJ: 866-315-0235
Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIAXLE-REAR LIFT
LENGTH (FEET)	48	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	104	STYLE	GENESIS	AXLE TO AXLE	60" - 60"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	54"
FRONT	0.150	S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
MIDDLE	0.150	GATESEAL	YES	PIN SETTING	36" W/ 3/8" KP
REAR	0.180 (REAR 15')	GATE LADDER	CENTER-LADDER	SUSPENSION	AAT30K/E2-1
POLISHED SIDES	YES	TARP HOOKS	NONE	SPRINGS	AIR (9)(10)(12)
ROOF	NONE	WINDERS	ONE-D/S	AXLES	TP - HXL-5
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
BULKHEAD	3/16"BUFFED(1)(5)	GATE CONTROL	MECH - BOLT CLAW	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO - (8)	ABS	2S / 1M
TARP	NONE		MIDDLE-SPRING	HUBS	10 S STEEL-GREASE
CATWALK	YES-INTERMEDIATE		REAR-TUBE	DRUMS	CAST
B.H. LADDER	D/S-LADDER	COMPACTOR:		WHEELS	8.25 X 24.5 (13)
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		6 STEEL/6 HP
FLOOR MAKE	KEITH-3.5" DRIVE	CENTER LATCH		TIRES	11R 24.5 R268
FLOOR MAT'L	2299 (6)(15)	PIN DIA.			ECOPIA 16PLY (14)
WEARPADS	CWS			DOLLIES	2 SPD JOST A451
TAPE COLOR	BLACK IN TOP RAIL	HYDRAULICS:		LOCATION	D/S CRANK (4)
LIGHT PANEL	LED IN TAILGATE	HOSES	TWO-4000 PSI	BUMPER	EAST UNDERRIDE
MARKER LIGHTS	LED (7)	LENGTH	108"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	YES - LED	FITTINGS	WINGNUT	PUSH BLOCKS	YES
MUDFLAPS	STD	HP	1" FEMALE	PAINT	EAST BLACK
HOSE HANGER	YES-ON BULKHEAD	LP	1" MALE (3)(11)		
TIRE CARRIER	NONE	HOSE LOCATION	P/S-REF 89223 (2)		
		AIR & ELECTRICAL	CENTER-REF 89223		

REMARKS:

1. NO INSIDE BULKHEAD STEPS.
2. AUXILIARY ISO 7 WAY PLUG
3. POLYCARNOATE BOX FOR FRAME SWITCHES - OLD STYLE
4. ADD TRUCKLITE REGISTRATION HOLDER TO D/S LANDING GEAR BRACKET.
5. MANDOOR IN CENTER OF BULKHEAD
6. T-BLOCKS @ REAR. DRIVE UNIT FLOOR OPENING MOVED FORWARD FOR TRIDEM. MAKE SURE DRIVE UNIT OPENING MISSES ALL AXLES - 54" REAR AXLE SETTING
7. 5 PR TOP & BOTTOM - NO PROTECTORS - TOP ROW 16" DOWN FROM TOP OF TOP RAIL
8. REAR CROSSPIPE MOVE FORWARD 1' FROM STANDARD PLACEMENT.
- 9.AAT30K MAIN TANDEM w/AAL30K/R3 LIFT AXLE BEHIND TANDEM.LIFT AXLE TO HAVE SWITCH IN BOX AND ELECTRIC CAB CONTROL OPERATIONS)
10. GALVANIZED SUSPENSION HANGERS.
11. RIGHT WEIGH OIL FILLED GAUGE IN LBS. FLUSH MOUNTED IN BULKHEAD ON D/S RADIUS FOR DRIVER VISIBILITY-REF 89223
12. LIFT AXLE TO HAVE BRAKE RELEASE.
13. STEEL INSIDE / ALUM OUTSIDE. USE WHEEL GUARD INSULATOR BETWEEN STEEL AND ALUMINUM WHEELS.
14. HENDRICKSON TIRE MAXX PRO ALL AXLES.
15. KEITH SPLASH GUARD HOLD DOWN BEARINGS
16. GALVANIZED 5TH WHEEL ASSEMBLY W/ REMOVABLE KINGPIN

OVERALL HEIGHT (FT)

13.25

EMPTY WEIGHT (#)

20,483

CUBIC YARDS

125

(EMPTY WEIGHT VARIANCE +/- 3%)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.