



A030832-A030840
TEMP VIN: S029719-S029727



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	TELESCOPIC SEMI-TRAILER, STEEL PLATFORM.
DIMENSIONS	
LENGTH	48'-0" closed.
LENGTH	80'-0" opened.
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61 1/4" high at front and 58" at rear.
COUPLING	
COUPLER PLATE	5/16", plug welded structure.
KING PIN LOCATION	24" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, (exterior), 3/8" x 6", 100 000 psi steel, 24" high.
FLANGES	Male section (interior), 1/2" x 6", 100 000 psi steel, 17 5/8" high. (For tandem suspension Only)
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
GOOSENECK	12" high, with integrated nose ramp and 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, galvanized. Bolted, 12" c/c. (for bolted construction)
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
SIDE RAILS	Galvanized 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Galvanized front and rear sills.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
DIAGONAL BRACES	2" x 2" x 3/16" angles, ** bolted ** in web and to a crossmember, each side.
X BRACES	Between main beams, full length, sheet metal with cutting holes at front and rear between male main beams.
LOCKS	Air operated with a third glad hand at front. *** with filter ***
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
SPACERS FOR RUB RAILS	Double between side boxes.
ENDS	
FRONT RAIL	Formed steel 1/4".
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
BUMPER	Aluminum plate, bolted between bumper uprights to close rear.
HEADBOARD	48" high, galvanized steel (G164), 4 uprights and top made of tubing and 10 gauge steel plate installed inside with retroreflective tapes.



ITEM	DESCRIPTION
POCKETS REAR RAIL	(this bulkhead is NOT D.O.T.) **** galvanized *** 2 welded pockets at front for removable headboard. 11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM TURN SIGNAL REAR ADD. CONNECTOR STROBE LIGHTS TAIL LIGHTS	7 way (SAE J560), Phillips brand. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, grounded to front connector, sealed beams Grote. (tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400). Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber. 4 way. Sealed beams (Grote LED #77353 strobe) amber. Qty: (1) each side. toggle switch installed: @ REAR Sealed beams (Grote DEL #54332) red. Qty: 1 additionnal each side. From outside, tail lights and flasher, flasher with parking, brake with parking.
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGS-4F115), with mounting plate, full galvanized. 10" x 11 1/2". Road side.
BOGIE BASIC SUSPENSION BOGIE SUSPENSION U-BOLTS SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS	Slider, Hutch H-9801, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension. 4" c/c between locating holes, (48" travel). Hutch H-9700, tandem, underslung, under mount, 49" spread. With nuts at bottom. 3 leaves, model TRA 2740 or 365-00, 12 000 lbs capacity. 5" round, 22 500 lbs. capacity. Welded. 28 splines. 77 1/2". Steel, bolted. 16 1/2" standard, extended life lining. HM 218248 and HM 212049. TSE S-ASA, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omni brake" (30-30). (4 years warranty by T.S.E. for parts only). 10 studs disc hubs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single wheels. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.



ITEM	DESCRIPTION
TIRES MANUAL STOP BAR(S)	Standard duty with standard steel. General, 11 R 22.5 HT+ 14 ply (41.1") One, Hutch.
AIR SYSTEM GLAD HANDS AIR VALVES VALVE	Fixed, filter on the third glad hand at front. Meritor Wabco, IABS, 2 sensors 1 modulator. Fast-brake kit.
ACCESSORIES REGISTRATION HOLDER WINCHES SLIDING TRACK MUD FLAPS	One plastic, Betts-PS-1 or equivalent. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (5 7/8"). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING PAINT BOGIE AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES SERIAL PLATE	Galvanized plateform. (no paint) Bogie painted same color as trailer. Code:gray PPG Q37-939514. Same color as trailer. code: gray PPG Q37-939514 Same color as trailer. White. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. V.I.N. plate to be stick on an aluminum plate riveted on the frame. (it doesn't stick on galvanized steel)
ADDITIONAL OPTIONS	estimated weight is 16,546 LBS +/- 3% same as U#233983 with removeable galvanized HB
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.