



Hale Trailer Brake & Wheel 031114-031123

Base Model: FB45-102 3xle Spring Fixed

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 45'

OVERALL WIDTH 8' 6"

KING PIN SETTING 30" - Tapered Front

UPPER COUPLER PLATE 5/16" (+)30#

5/16" Plate.

UPPER COUPLER HEIGHT 48"

BULKHEAD None

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

SIDE RAILS 6" - 6.5# Per Foot

FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg. (+325#)

COIL HAUL PACKAGE None

FLOOR DECKING 1-1/8" Apitong

WINCH TRACK None

WINCHES None (-108#)

STRAPS None

LANDING GEAR Holland Mark V

SUSPENSIONS Spring Ride - Hutchens 3 Axle

SUSPENSION LOCATION Back Edge of Rear Tire Set 30" From Rear of Trailer

LIFT AXLE None

DUMP VALVE None

SCALES None

AXLES (3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS -

5/8" Wall Axles.

23K Brake Lining.

Parallel Spindles.

ABS SYSTEM ABS System 4S/2M

AXLE SPACING 49" (+35#)

PARKING BRAKES All Axles

DUST SHEILDS None

TIRE INFLATION SYSTEM None

TIRES 11R22.5 - Double Coin **16Ply.**

Must Be 16 Ply Tires Load Range H.

RR150 Deep Tread.

WHEELS Disc - Hub Piloted - 22.5 Steel

ANTI-SAIL MUD FLAPS Behind All Axles

STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear

RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape

PIPE SPOOLS Double

DOCK BUMPERS Rubber Inboard

CARGO TIE DOWN Recessed "D" Rings - 13 Pair

TOOLBOX MATERIAL None

TOOLBOX TYPE None

TOOLBOX LOCATION None

TIRE CARRIERS None

CONTAINER TWIST LOCKS None

LIGHTS Sealed Wiring Harness W/LED Pkg-Micro(2)Front/(2)Rear Sides-3 Ctr Rear

CUSTOM LIGHTS None

PAINT Red

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.