

HALE

TRAILER

BRAKE & WHEEL



A031241-A031249
VIN: S030114-S030122

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Velocity 53' Spring Slider (Model Code: HAVSF22SST)

Length / Width: 53 feet x 102 inches

Suspension Type: Sliding spring tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Flooring: 1 1/8 inch wood

Crossmembers: 12 inch centers - 4 inch jr. I-steel

Side Rails: 6 inch structural channel @ 6.5 lbs/ft

Stake Pockets: 3/16 inch steel on 24 inch centers

Pipe Spools: Double between stake pockets

Rubrail: 3/8 inch x 2 1/2 inch steel

Main Beams: 130K load bearing flanges

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM Standard with Forward & Rear Bracing

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkheads: Removable Aluminum 4 post DOT type bulkhead - no turnback - 48 inches high

Bulkhead Pockets: 4 - F-5 DOT-type steel

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed

ABS: Meritor Wabco iABS 2S/1M BASIC - no cable or tool (*Fontaine recommends 4S/2M)

Axle Spread: 49 inches (C/L kingpin to C/L rear axle in front position is 40 feet or less)

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Oil in hubs

Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 11R 22.5 14PR OEM standard tires

Tire Inflation System: None standard

Suspension Detail: OEM Standard 3-leaf spring slider - 60 inches adjustable

Front Corners: Tapered

Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD

Paint: Black urethane with Velocity decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed on rubrails

Bumper: Weld-on type - meets underride requirements

Mudflaps: 1 set OEM standard behind rear axle

Spare Tire Carrier: None standard

Winch Track: Steel on road side

Sliding Winches: 12 ZINC Finish

27 foot Winch Straps: None standard

30 foot Winch Straps: None standard

Dock Bumpers: 1 pair rubber on rear

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.