

HALE TRAILER BRAKE & WHEEL



A031259-A031270

VIN: S030132-S031270

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Infinity Flat 53' Rear Axle Slide (Model Code: HAICF22RSA)

Length / Width: 53 feet x 102 inches

Suspension Type: Rear axle slide; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads

Flooring: 1 1/8 inch aluminum with 4 wood nailer strips

Crossmembers: 12 inch centers - 4 inch jr. I-steel

Single Coil Hauling Package: Included

Side Rails: Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

Chain Cargo Tie Downs: 17 pair recessed in siderails

Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

Rubrail: Integrated with siderail

Main Beams: 130K load bearing flanges

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM Standard with Forward & Rear Bracing

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front

Bulkheads: Removable aluminum 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed

ABS: Meritor Wabco iABS 4S/2M - no cable or tool

Axle Spread: 122 inches open - 54 inches closed - Meets California, Canadian RTAC and BC dimensional specifications in closed position

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 4 steel disc inside wheels - 4 aluminum High Polish outside with 4 Spacers

Tires: 11R 22.5 14PR OEM standard tires

Tire Inflation System: None standard

Suspension Detail: Hendrickson AANT23K and AAZNT23K Intraax air ride

Air Assist Slide Box Pins: Standard mount of controls on slider frame

Auto Glad Hand Dump : Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Air Lift: Lift Not Included: *On Front Axle Only Install Hendrickson UBL-401 Front Bolt-on Suspension Hanger Brackets (LH C-32038-1C & RH C-32038-2C) & Weld-on Lift Brackets (LH C-28617-1 & RH C-28617-2); Install Appropriate K-Brace To Fit Around These Brackets

Front Corners: Tapered steel

Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD

Paint: Black urethane on steel parts with Infinity decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails

Bumper: Weld-on type - meets override requirements - painted steel

Mudflaps: 1 set OEM standard behind rear axle only

Spare Tire Carrier: None standard

Winch Track: Full length integrated double L type aluminum on both sides -- STANDARD

Sliding Winches: (15) ZINC Finish: 8 Road Side, 7 Curb Side with Sliding Rope Hook/Winch Strap Hook Retainers

27 foot Winch Straps: None standard

30 foot Winch Straps: None standard

Dock Bumpers: 1 pair rubber on rear

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.