

# HALE TRAILER BRAKE & WHEEL



A031295-A031364  
VIN: S030168-S030237

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

### Velocity 48' Spring Slider (Model Code: HAVSF12SST)

**Length / Width:** 48 feet x 102 inches

**Suspension Type:** Sliding spring tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

**Frame Rating:** 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

**Flooring:** 1 1/8 inch wood

**Crossmembers:** 12 inch centers - 4 inch jr. I-steel

**Side Rails:** 6 inch structural channel @ 6.5 lbs/ft

**Stake Pockets:** 3/16 inch steel on 24 inch centers

**Pipe Spools:** Double between stake pockets

**Rubrail:** 3/8 inch x 2 1/2 inch steel

**Main Beams:** 130K load bearing flanges

**Kingpin:** 30 inches

**Loaded Fifth Wheel Height:** 49 inches

**Landing Gear:** OEM Standard with Forward & Rear Bracing

**Knee Braces:** Fabricated on approx. 60 inch C/C

**Bulkheads:** Removable Aluminum 4 post DOT type bulkhead - no turnback - 48 inches high

**Bulkhead Pockets:** 4 - F-5 DOT-type steel

**Number of Axles:** 2

**Axle Spindle:** Tapered

**Brakes:** Spring brakes, auto slacks

**Air Line Filters:** (2) Meritor In-line type installed

**ABS:** Meritor Wabco iABS 2S/1M BASIC - no cable or tool (\*Fontaine recommends 4S/2M)

**Axle Spread:** 49 inches

**Hub and Drums:** 10-hole hub-piloted with outboard cast drums

**Wheel Ends:** Oil in hubs

**Wheels:** 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

**Tires:** 11R 22.5 14PR OEM standard tires

**Tire Inflation System:** None standard

**Suspension Detail:** OEM Standard 3-leaf spring slider - 60 inches adjustable

**Front Corners:** Tapered

**Electrical System:** LED: 3 lights/side, 3 lights/side on rear - STANDARD

**Paint:** Black urethane with Velocity decals - STANDARD

**Conspicuity Tape:** Per NHTSA specs - installed on rubrails

**Bumper:** Weld-on type - meets underride requirements

**Mudflaps:** 1 set OEM standard behind rear axle

**Spare Tire Carrier:** None standard

**Winch Track:** Steel on road side

**Sliding Winches:** 12 ZINC Finish

**27 foot Winch Straps:** None standard

**30 foot Winch Straps:** None standard

**Dock Bumpers:** 1 pair rubber on rear

**Hubodometer:** None standard

**Registration Holder:** Install registration holder - OEM standard

**Tool Box:** None standard

**VIN Plate:** Bilingual US/Canadian VIN plate

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.