

# HALE

## TRAILER

### BRAKE & WHEEL



A031672-A031686  
VIN: P3682-P3696

#### SALES | RENTALS | PARTS | SERVICE

|                                       |                                      |
|---------------------------------------|--------------------------------------|
| <b>Allentown, PA:</b> 800-383-8894    | <b>Little Rock, AR:</b> 833-424-8944 |
| <b>Baltimore, MD:</b> 888-601-7500    | <b>Portland, ME:</b> 800-325-4253    |
| <b>Concord, NC:</b> 800-438-2250      | <b>Raleigh, NC:</b> 833-418-9777     |
| <b>Delmar, DE:</b> 866-486-1400       | <b>Scranton, PA:</b> 800-569-1400    |
| <b>Des Moines, IA:</b> 888-673-5011   | <b>Springfield, MA:</b> 800-854-5306 |
| <b>Elkton, MD:</b> 800-544-7127       | <b>Voorhees, NJ:</b> 866-315-0235    |
| <b>Jacksonville, FL:</b> 800-828-3055 | <b>Walpole, MA:</b> 800-854-5310     |

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

| Magnitude 302 Jeep GEN 3 (Model: 302JEEP)                                                                                                 |                         |
|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
|                                                                                                                                           | Est. Wt.: 5865 # +/- 3% |
| <b>Capacity:</b> 30 tons GAWR and tire rating determine legal loads                                                                       |                         |
| <b>Length (Jeep Only):</b> 17 feet 11 inches                                                                                              |                         |
| <b>Width:</b> 8 feet 5 inches                                                                                                             |                         |
| <b>Compatibility:</b> Magnitude 55H or Magnitude 55L Plus with optional 35-inch flip box                                                  |                         |
| <b>Gooseneck Design:</b> Fixed Narrow Width                                                                                               |                         |
| <b>Loaded Fifth Wheel Height:</b> 48 in.                                                                                                  |                         |
| <b>Swing Radius</b> 94 in.                                                                                                                |                         |
| <b>Deck Design:</b> Beam design                                                                                                           |                         |
| <b>Fifth wheel:</b> OEM Standard, 12 in. slide adjustable, 57.5 inches fifth wheel height                                                 |                         |
| <b>Number of Axles:</b> 2                                                                                                                 |                         |
| <b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.  |                         |
| <b>Axle Spread:</b> 49 inches (between axles)                                                                                             |                         |
| <b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount <b>Spring Brakes on Axle 1</b> |                         |
| <b>Dust Shields:</b> None                                                                                                                 |                         |
| <b>Suspension:</b> Air ride                                                                                                               |                         |
| <b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs                    |                         |
| <b>Supports:</b> Single Telescopic                                                                                                        |                         |
| <b>ABS:</b> Not required                                                                                                                  |                         |
| <b>Load Scale:</b> None                                                                                                                   |                         |
| <b>Tires:</b> 275/70R 22.5 H ply OEM Standard                                                                                             |                         |
| <b>Wheels:</b> 8.25 x 22.5 Outer Lvl one buffed wheels/ steel disc - hub-piloted inside                                                   |                         |
| <b>Hubodometer:</b> None                                                                                                                  |                         |
| <b>Tire Inflation:</b> Tire Inflation Installed Tiremaxx Pro                                                                              |                         |
| <b>Electrical System:</b> DOT sealed beam and harness                                                                                     |                         |
| <b>Additional Marker Lights:</b> None                                                                                                     |                         |
| <b>Paint:</b> Fontaine black polyurethane enamel                                                                                          |                         |
| <b>VIN Plate:</b> Bilingual VIN plate                                                                                                     |                         |
| <b>Registration/Document Holder:</b> Registration/document holder intalled                                                                |                         |

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.