

A031690-A031694 VIN: 44943, 44945-44948

SALES RENTALS PARTS SERVICE

Little Rock, AR: Allentown, PA: 800-383-8894 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer 👔 🛐

800-232-6535 *FINANCING

Model: Axle Attachment Capacity in tons:

1. DESIGN PARAMETERS

Flip-up & removable Type

Fabricated Framework Suspension Ridewell air

Axle attachment connections Attachment to be equipped with top and bottom connecting ears, pin tubes with

bolts and nuts, shims, chrome tapered connecting pins, air and electrical

connections

Axle capacity 25,000# - GAWR 24,700# Brakes 16-1/2" x 7" air actuated

Wheels Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil

seals, inner wheels steel with outer aluminum wheels polished

Anti-lock brake system None

Tires Four (4) 275/70R22.5 (H) 16PR radials

8'-6" Bridge width

Axle frame height 41" frame; 37" bolster Half bolster With flag holder slots Lash rings 2 at rear bent style

Lights and wiring 12 volt system with the following:

> All lights to be LED excluding license plate light All marker/I.D. lights to be 3/4" bullet style

4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired

to switch on marker light circuit Strobe lights with switch at rear Wire for battery back-up

Paint Valspar standard Talbert black, R-Cure 800 series paint with ZINC RICH primer Mudflaps

Talbert anti-sail

Additional design specifications 1) 2 rubber bumpers on top

2) 54" axle spacing 3) Over ride chains

4) Estimated empty weight: 2,850#

With existing Talbert Trailer, 55SA or 55CC Compatibility