



A031835-A031839
VIN: 237901-237905



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	TAG-ALONG
DIMENSIONS	#202874
LENGTH	36'-0" overall, 24'-0" for the floor.
WIDTH	102", full width side rail to side rail.
HEIGHT	Floor at 35" high (235/75 R17.5 tires)
COUPLING	
COUPLER PLATE	Pole with draw bar.
KING PIN LOCATION	Eye hook must be adjustable between 19 3/4" & 31" high. (2 1/4" between each adjustment holes)
STRUCTURE	**CAMBER: 3/4"***
FLANGES	3/8" x 4", 100 000 psi steel.
WEB	3/16", 80 000 psi steel. 16" high.
GOOSENECK	16" high X 78" long (at center of the draw bar).
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 12" centre to centre, installed with stiffeners angles.
FLOOR	Apitong or equivalent, 1 5/16" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember. (for galvanized platform)
SIDE RAILS	Formed channel 7" @ 9.8 lbs/ft.
SIDE BOXES	None.
RUB RAILS	None.
X BRACES	Between main beams, full length.
FENDERS	Over tires at rear, **anti-skid plate 1/4"***.
ENDS	
FRONT RAIL	3/16" formed steel.
HEADBOARD	**15"*** high, steel.
REAR RAMP	Loading ramp to load vehicules. 1 5/16" Apitong floor.
PNEUMATIC RAMPS	(2) non sliding pneumatic ramps, **40"*** wide x 72" long. 1 5/16" Apitong floor. Locked in vertical position when not in use. (add a pin to secure the ramps control box)
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560), Phillips brand.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams, (tail lights with male pins #53962, markers Micro-Nova #49332, 49333, (2) licence light #60280-M).
TURN SIGNAL	Sealed beams LED, (Grote #54163), one lamp including side marker and flasher, each side at middle point, amber.
REAR ADD. CONNECTOR	4 way. (for strobe light)
MAIN SYSTEM	One junction box installed at rear with special double harness.
REAR ADD. CONNECTOR	
ALARM (PNEUMATIC RAMPS)	Model Grote #73250, with activation button installed in the same control box just beside the buton of the activation of the ramps.



ITEM	DESCRIPTION
	Add the sticker 303-8767 in the box above the button of the alarm.
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGS-4F115), with mounting plate, fully galvanized. 10" x 11 1/2". Road side.
BOGIE BOGIE SUSPENSION	Fixed. Hutch H-9700, tandem, underslung, undermount, 49" spread.
U-BOLTS LIFT SUSPENSION	With nuts at bottom. Hendrickson HT-250US (6.5) with Manac center lift. Located at 49 " ahead of tandem. Controlled manually.
SPRINGS AXLE(S)	3 leaves, model TRA 2740 or 365-00, 12 000 lbs capacity, and air bags. Hendrickson, HN-S505, 25 000 lbs. capacity. (12 1/4" brakes)
SPIDERS CAM SHAFTS TRACK	Welded. 28 splines. 77 1/2".
DUST SHIELDS BRAKES BEARINGS	None. 12 1/4", H20HXS lining. HM 218248 and HM 212049.
SLACK ADJUSTERS SEALS BRAKE CHAMBERS	Haldex, automatic, 28 splines, curved (6"). Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30), long stroke. (4 year warranty on parts only)
HUBS AND DRUMS	Webb, 8 stud disc hubs, drums 89 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
RIMS	Alcoa, aluminum, "LvL ONE" finish and half made of steel, 17.5 x 6.75, disc (8 holes), 275mm B.C., single flange nuts.
SPACERS TIRES	Wheel guard 10 holes. Located between two wheels. Continental, 235/75 R 17.5 HTR-2 16 ply (31.4")
AIR SYSTEM GLAD HANDS AIR VALVES CONTROL BOX AIR TANK EXTRA AIR TANK	At front. (with filter) Meritor Wabco, ABS, 2 sensors 1 modulator. Stainless steel. Add one aluminum air tank (3100 PO/CU) to operate the ramps.
ACCESSORIES TIRE CARRIER REGISTRATION HOLDER WINCHES LASHING RINGS	Qty: 1, bolted, galvanized, located nearby landing gear, mouth curb side. (tag-along #236462) One plastic, Betts-PS-1 or equivalent. No winch nor straps nor sliding track. Qty: 16, "D" type steel rings welded to frame, (Buyer B-5055) Located: (7) on each side, (6) on main deck, (1) at beavertail and (2) on main beam at the front headboard.



ITEM	DESCRIPTION
STORAGE BOX(ES) MUD FLAPS R	(1) included at draw bar, hole plate at bottom and cover at top. One set, rubber with Manac logo and vertical grooves to reduce spray. **NOTE** Install steel plate with holes at bottom of the front pole to have a storage area for the glad hands and the connector.
FINISHING PAINT HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES SERIAL PLATE	Galvanized plateform. (no paint) Black. Aluminum/White (powder coat) Installed on an aluminum flat bar which will be rivetted on the side rails. V.I.N. plate to be stick on an aluminum plate riveted on the frame. (it doesn't stick on galvanized steel)
ADDITIONAL OPTIONS MISCELLANEOUS	MDO

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.