

# HALE

## TRAILER

### BRAKE & WHEEL



**A031844-A031849**  
**VIN: 25580-25585**

SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	<b>800-383-8894</b>	<b>Little Rock, AR:</b>	<b>833-424-8944</b>
<b>Baltimore, MD:</b>	<b>888-601-7500</b>	<b>Portland, ME:</b>	<b>800-325-4253</b>
<b>Concord, NC:</b>	<b>800-438-2250</b>	<b>Raleigh, NC:</b>	<b>833-418-9777</b>
<b>Delmar, DE:</b>	<b>866-486-1400</b>	<b>Scranton, PA:</b>	<b>800-569-1400</b>
<b>Des Moines, IA:</b>	<b>888-673-5011</b>	<b>Springfield, MA:</b>	<b>800-854-5306</b>
<b>Elkton, MD:</b>	<b>800-544-7127</b>	<b>Voorhees, NJ:</b>	<b>866-315-0235</b>
<b>Jacksonville, FL:</b>	<b>800-828-3055</b>	<b>Walpole, MA:</b>	<b>800-854-5310</b>

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

## XL SPECIALIZED TRAILERS

### XL 80 Mechanical Full-Width Gooseneck

OVERALL LENGTH	53'
OVERALL WIDTH	102"
CAPACITY	80,000 LB DISTRIBUTED; 70,000 LB IN 16'
WEIGHT +/- 3%	0,000 LB
<b>GOOSENECK</b>	
LENGTH	10' FULL-WIDTH NECK
KINGPIN SETTING	16"
SWING CLEARANCE	84"
5TH WHEEL HEIGHT	50" - CUSTOMER TO CONFIRM
DECKING	1 1/8" APITONG DECKING, FLUSH
D-RINGS	( 2 ) BENT D-RINGS PER SIDE ( 3 ) PAN STYLE PER SIDE, ONE IN EACH CORNER, 3RD PAIR EVENLY SPACED BETWEEN ALUMINUM MUD FLAPS
MUD FLAPS	ALUMINUM MUD FLAPS
TOOL BOX	TOOL BOX ON BASE OF NECK WITH ALUMINUM LOCKABLE LID - RACK AND WORK LIGHT REGISTRATION HOLDER
<b>MAIN DECK</b>	
LENGTH	30' 4"
LOADED DECK HEIGHT	16" W/ 4" GROUND CLEARANCE
DECKING	1 1/8" APITONG DECKING, FLUSH
CROSSMEMBER	6" & 4" JR I-BEAM ON 12" ALTERNATING CENTERS
BEAMS	( 4 ) 12" FAB I-BEAMS
D-RINGS	( 8 ) BENT D-RINGS PER SIDE ( 4 ) PAN STYLE D-RINGS PER SIDE
OUTRIGGERS	REMOVABLE SWINGOUT OUTRIGGERS ON 24" CENTERS
RAMPS	TAPERS TO 4"
CHAIN DROPS	24" CENTERS - OUTSIDE BEAMS
<b>REAR DECK</b>	
LENGTH	12' 8"
LOADED DECK HEIGHT	38" - SET RIDE HEIGHT 2" HIGHER THAN STANDARD
AXLES	( 3 ) 25,000 LBS. NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY/ AIR RIDE
AXLE SPACING	49"
ABS	4S2M WITH SPRING BRAKES ON ( 2 ) AXLES
TIRES	245 / 70R / 22.5 ( J )
WHEELS	8.25 X 22.5 10-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE, STEEL INSIDE DISC
BRAKES	16 1/2" X 7"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH ( 3L +5L + 3L ) DUAL INTENSITY TAIL LIGHT ALUMINUM PACKAGE 4" AMBER STROBE IN THE 4TH AND 8TH POSITION. 4" TURN AND MARKER IN 1ST AND 11TH POSITION 4" STOP AND MARKER LIGHTS IN THE 2ND, 3RD, 5TH, 6TH, 7TH, 9TH, AND 10TH POSITION
DECKING	1 1/8" APITONG DECKING, FLUSH
D-RINGS	( 3 ) PAN STYLE PER SIDE, ONE IN EACH CORNER, 3RD PAIR EVENLY SPACED BETWEEN ( 2 ) FLAT D-RINGS ON EACH MAIN BEAM OF REAR TRANSITION, ONE AT TOP, ONE AT BOTTOM ( 2 ) BENT D-RINGS IN TAIL CHANNEL
<b>PAINT</b>	BLACK
<b>ADDITIONAL</b>	TRIPLE DONUT FRONT CONNECTOR PLATE MANUAL RIDE HEIGHT CONTROL MANUAL DUMP VALVE ( 2 ) PAIR OF EZ MOUNT FLAG HOLDERS ( 9 ) TOTAL TRUCKLITE LIGHTS AND CONNECTORS ( 2 ) ON UPPER DECK, ( 4 ) ON MAIN DECK AND ( 2 ) ON REAR DECK (REAR CLEARANCE LIGHTS TO BE BEEHIVE LOOK LOOM AROUND TRUCKLITE LIGHTS AND CONNECTORS LIGHTS AND WIRING ABOVE CROSSMEMBERS LIQUID FILLED AIR GAUGE AIR LIFT ON REAR AXLE GLADHAND DUMP VALVE ( 2 ) TK STYLE CHAIN SLOTS PER SIDE ON SIDE PLATES IN LIEU OF LIGHTENING HOLES ( 2 ) TK STYLE CHAIN SLOTS BETWEEN EACH SET OF AXLES LESS DROP IN WHEEL AREA THAN STANDARD

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.