

A032221-A032270 VIN: P54573-P55078

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: Little Rock, AR: 800-383-8894 833-424-8944 **Baltimore, MD:** 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: Raleigh, NC 833-418-9777 800-438-2250 Delmar, DE: Scranton, PA: 800-569-1400 866-486-1400 Des Moines, IA: Springfield, MA: 800-854-5306 888-673-5011 Voorhees, NJ: Elkton, MD: 800-544-7127 866-315-0235 Jacksonville, FL: Walpole, MA: 800-854-5310 800-828-3055

haletrailer.com | @haletrailer f 🕑 🛅 🎯 🛗

800-232-6535 *FINANCING AVAILABLE

MP20P | Chassis Trailer

20-40' City Combo Intermodal Chassis

weight: 7,780 lbs | length: 29' 11"

General	This Chassis Is Designed For Transporting 40' or 20' ISO Dry Container. This Chassis Meets All DOT, AAR, ANSI, TOFC, FMVSS, SAE And TTMA Specifications			
Feature	Description	Weight (lbs)	Length (in)	
Overall Length	29'-11" Retracted or 40'-10" Extended	0.00	0.00	
Overall Width	96"	0.00	0.00	
Overall Height	58"	0.00	0.00	
Fifth Wheel Height	48 +/- 1"	0.00	0.00	
Rear Deck Height	48 +/- 1"	0.00	0.00	
King Pin Location	24" From rear face of front bolster	0.00	0.00	
Axle Spacing	49"	0.00	0.00	
Payload	44,800 lbs in 20' position; 67,200 lbs in 40' position	0.00	0.00	
Main Frame	Fabricated I-beam with high strength Grade 100 steel flanges.	0.00	0.00	
Cross Member	Fabricated 3/16" thick channel with profiled bar type diagonal brace.	0.00	0.00	
Upper Coupler	5/16" pick up plate with 2" diameter king pin	0.00	0.00	
Rear Bumper	4" x 4" square tube step	0.00	0.00	
Front Locking Pin	Toca or Buffers	0.00	0.00	
Center Twist Lock	Toca or Buffers	0.00	0.00	
Rear Twist Lock	Toca or Buffers	0.00	0.00	
Locking system	Air operated locking pins, Activated on both sides of the trailer through third glad hand on front sill.	0.00	0.00	
Landing Gear	60,000 lbs. capacity 2-speed 19" travel with low T shoes	0.00	0.00	
Suspensions	Spring Ride- Mechanical w/ Heavy Duty High Arch 3-Leaf Springs	0.00	0.00	
Axles	(2) 5" round with 22,500lbs at 71.5" track	0.00	0.00	
Lubricant	Synthetic Semi-fluid grease lubricant.	0.00	0.00	
Wheels	(8) 10 HOLE HUB PILOTED 22.5 STEEL WHEEL	0.00	0.00	
Tires	(8) Radial 11R22.5	0.00	0.00	

Brake System	16.5"X 7" Quick Change Brakes. WABCO 2S/1M ABS, SEALCO 110500 SPRING BRAKE, 5.5" 28 SPLINE ASA, TYPE 30/30 BRAKE CHAMBER.	0.00	0.00
Electrical	Phillips QCSII Wiring Harness w/GPS Drop-Out. Phillips LED Limited Life time	0.00	0.00
Document Holder	None	0.00	0.00
Paint	Fleet Black With Zinc Rich Primer and Urethane Topcoat	0.00	0.00
Tire Inflation	Yes	0.00	0.00
Hub odometer	None	0.00	0.00
Anti-Sail Mud Flaps	Pitts Trailers Branded White	0.00	0.00