



PHA A032325-A032326

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: Raleigh, NC 800-438-2250 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer **f** 

0





800-232-6535

\*FINANCING AVAILABLE

## A110HDG-E (Alpha Series Hydraulic Detachable Extendable)

Capacity 110,000 lbs. Open in 2 point rigid load base

 Concentrated
 110,000 lbs. in 16' Closed

 OAL
 53'
 OAW
 102"

Gooseneck 10' 5" Hydraulic Detachable Sub Frame

51" 5th Wheel Height 14' 1" Long

15" King Pin 39" Loaded Deck Height

80" Swing Clearance32 Degree Rear Transition5 Position Ride Height AdjustmentOpen Wheels with Bolsters

3' Flip Neck Connection Chain Slots in Each Bolster
3' Flip Neck(116" Swing) 2 Flat D-Rings at Rear

LED Work Light Flag Holders

1 pair Stake Pockets in Tail Channel

Main Deck 28' 7" Closed- 50' Open Frame Reinforcement for Single Axle

28' 7" Closed- 50' Open Frame Reinforcement for Single Axle
14" Fabricated I-Beams Stinger

20" Loaded Deck Height

6" Ground Clearance Axles and Suspension
Cross Members ALT on 12" Centers 3 - 25,000 lb Axles

8 Bent D-Rings per Side 54 1/2" Axle Spacing
Chain Slots on 24" Centers each side Ridewell Suspension
1 3/4" Apitong Raised Decking-Full Width 16 1/2" x 7" Drum Brakes

Upper Flange Reinforment Spring Brakes on Two Axles

Front Flip Ramps Raise & Lower Valve

Full Depth Removable Swingout Outriggers Manual Ride Height Control

Air Operated Lock Pin, Deck opens every 2' Air Lift on 3rd Axle

Toolbox W/Lid In Rear of Male Deck Section Airweigh Quickweigh Scale

255/70R22.5 Tires

Suspension Controls in Bolster

Lighting

2 Tail Light Package with Stainless Steel Covers 2 Pr. Side Markers/1 Pr. Mid-Turn on Deck Grote Ultra Blue-Seal Wire Harness

Gooseneck	Sub Frame
13 hp Honda in base section/Dual Operation	UHMW Poly Wheel Covers
Main Deck	275/70R22.5 tires
2 Pr Additional Clerance Lights	Polished Aluminum Outer Wheels
Paint	Nitrogen Stinger Top Lugs
Black	3rd tail light package with strobe (no battery)
	Battery back for strobe with 4-way plug for FA