

HALE

TRAILER

BRAKE & WHEEL



A032382-A032384
VIN: 44968-44970

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: AC-20
Capacity in tons: 20

1. TONGUE

Pintle eye
Tongue

Adjustable pintle eye (3" ID) with 48" chain and grab hooks
5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward

Drop leg

2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard

Electrical receptacle
Headboard

Seven pin connector
8" high full width

2. DECK

Deck section design
Deck section length
Deck section width
Loaded deck height
Flooring
Lash rings

One piece tongue, main beam and beavertail (cold formed)
27'-0" (21'-0" flat with 6'-0" beavertail)
8'-6"
32-1/4"
1-1/2" apitong - individual wheel well covers
10 total -
4 each side on flat deck (straight style), 8 total
1 each side on beavertail (straight style), 2 total

Mainbeams
Crossmembers
Sidemembers
Beavertail
Ramps

12" deep hi-tensile
6" deep hi-tensile
8" deep hi-tensile
6'-0" Double break with wood flooring full width
6'-0" with wood flooring with 3 springs per ramp and grab handles

3. RUNNING GEAR

Number of axles
Axle capacity
Brakes
Wheels
Tires

2
25,000# Full width track
12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.
Steel disc with oil seals (6.75 x 17.5)
Eight (8) 215/75R17.5 (H) 16PR radials
Use valve stem extensions on inside wheels
44,800# Hutch spring

Suspension

4. GENERAL

Lights and wiring

12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK

Paint

Valspar standard Talbert black, R-Cure 800 series paint

Additional general specifications

Formed step in front of 1st axle both sides of trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.