

# HALE

## TRAILER

### BRAKE & WHEEL



**A032403-A032407**  
**VIN: D48148-D48152**

#### SALES | RENTALS | PARTS | SERVICE

|                   |              |                  |              |
|-------------------|--------------|------------------|--------------|
| Allentown, PA:    | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD:    | 888-601-7500 | Portland, ME:    | 800-325-4253 |
| Concord, NC:      | 800-438-2250 | Raleigh, NC:     | 833-418-9777 |
| Delmar, DE:       | 866-486-1400 | Scranton, PA:    | 800-569-1400 |
| Des Moines, IA:   | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD:       | 800-544-7127 | Voorhees, NJ:    | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA:     | 800-854-5310 |

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

Base Model #: DC53BTR x 102 Air Spread 22.5

Serial #: 48148 - 48152

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 53' - Base Weight 13,000# - Including Length of Beavertail

UPPER DECK LENGTH 10' Length = 59" Height

LOWER DECK LENGTH 38' Length = Front 41", Center 42" Rear 40" Heights

DOVETAIL 60"- 15\* DEGREE TRANSITION - STEEL W/ TRACTION BARS

\*\*Rear End Set Up For Future 3rd Ramp Install.\*\*

OVERALL WIDTH 8' 6"

KING PIN SETTING 18" - Squared Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

MAINFRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg 3/8"x 5" Top & 1/2" x 5" Bottom & 3/16" Web)

BULKHEAD None

SIDE RAILS 6"-Alum-Extruded W/Double L Track

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

\*\*Galvanized Crossmembers.\*\*

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

\*\*Galvanized Crossmembers.\*\*

COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Silks-Ctr On Trailer

FLOOR DECKING 1-1/8" HD Aluminum W/2 Nailer Boards

WINCHES 12

WINCH TRACK Double L Aluminum - Extruded Siderail C/S & R/S - Bothsides

\*\*Tie Bar Both Sides.\*\*

STRAPS None

LANDING GEAR Two Speed

SUSPENSIONS Air Ride - Hendrickson Intraax 23K - Fixed

SUSPENSION LOCATION King Pin to Center of Rear Axle 43'

AXLES (2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires

AXLE SPACING 10'2" Wide Spread

DUMP VALVE Manual-Position In Rear Skirt Gusset D/S-Dump All Axles

LIFT AXLE None

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Pilot-22.5 (2-AX)-Polish ALUMINUM 4 Outside Wheels(4-Steel Inside) (-148#)

TIRES 255/70R 22.5 - Firestone

TIRE INFLATION SYSTEM None

STAKE POCKETS 24" O.C. & 4 Across Front

ANTI-SAIL MUD FLAPS Behind All Axles

PIPE SPOOLS Double

RUB BAND STEEL 3/8" x 3" - Aluminum - Recessed for DOT Tape

DOCK BUMPERS None

LOADING RAMPS (2)-Spring Assisted

**\*\*Galvanized Ramps.\*\***

CONTAINER TWIST LOCKS None

CARGO TIE DOWN Recessed Chain Tie Downs - 14 Pair

TIRE CARRIERS None

TOOLBOX MATERIAL Aluminum Smooth Box and Doors

TOOLBOX TYPE 18Hx18Dx60L-Alum Box-Barn Style Double Door-Cam Lock Alum Door

TOOLBOX LOCATION Driver Side- Between Spread

LIGHTS Accent Total LED Package with Strobe Pkg in Rear (4/3/4)

**\*\*5 Total Markers Per Side.\*\***

**\*\*Rear Strobes With Toggle Switch.\*\***

CUSTOM LIGHTS None

PAINT Black - Sherwin Williams Epoxy Primer and Acrylic Polyurethane - Shot Blasted

CUSTOM 1. Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle

**\*\*Rear Axle Dump By Aux. 7-Way and Manual Dump All Axles.\*\***

CUSTOM 3. Grote Document Holder Landing Gear R/S

CUSTOM 2. None

Reference SN # 44506

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.