

HALE

TRAILER

BRAKE & WHEEL



A032416-A032417
VIN: 44958-44959

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: AC3-30-AR (air)

Capacity in tons: 30

Pintle eye
Tongue

Adjustable pintle eye (3" I.D.) with 48" chain and grab hooks
5'-6" with lockable tool box with aluminum diamond plate lid
Move hinge 4" forward

Landing Gear

2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard

Electrical receptacle

Seven pin connector

Headboard

8" high full width

Deck section design

One piece tongue, main beam and beavertail (cold formed)

Deck section length

30'-0" (24'-0" flat with 6'-0" beavertail)

Deck section width

8'-6"

Loaded deck height

33-3/4"

Flooring

1-1/2" apitong

Individual wheel covers with wood between and behind them

Lash rings

20 total -

8 each side on flat deck (straight style), 16 total

1 each side on beavertail (straight style), 2 total

1 each side on top of main beams, just behind headboard (swings front to back) (straight style), 2 total

Main beams

12" deep hi-tensile

Cross members

6" deep channel x 8.2# hi-tensile

Side members

8" deep hi-tensile

Beavertail

6'-0" Double break with wood flooring full width

Ramps

38" wide x 6'-6" length air ramps with wood flooring, stored vertically with lock bar

Number of axles

3

Axle capacity

25,000#, full width track

GAWR = 21,420#

Brakes

12-1/4" x 7-1/2" air with 2S/1M ABS, type 30 chambers/6" auto slacks. Spring brakes on two axles.

Wheels

Aluminum/steel disc with oil seals (6.75 x 17.5), inner wheels steel, outer aluminum wheels polished

Tires

Twelve (12) 235/75R17.5 (H) 16PR radials

Use valve stem extensions on inside wheels

Suspension

Air ride with air lift on axle 1

Air lift switch located on tongue

50,000# Hutch spring on axles 2 & 3, spring 365-00

Lights and wiring

12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK

strobe lights mounted in rear ramps with switch in tool box (Ref. SN44570)

Paint

Valspar standard Talbert black

Estimated empty weight

12,660#

Additional general specifications

Formed step in front of 1st axle both sides of trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.