

Item HYDRAULIC DETACHABLE GOOSENE	ECK Description Model: RTN55TD3-PS TRAILER
TONS CAPACITY	55 TONS IN ANY 12'
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL
CUSTOM/PAVER SPECIAL	TAPERED FRONT BEAMS (8-3/8" DEEP)
PLATFORM WIDTH	8'-6"
PLATFORM LENGTH	24' (MUST HOLD 53' O.A.L.), NOT TO EXCEED 43'-0" FROM THE 84" KINGPIN TO THE CENTER OF THE 2ND AXLE
PLATFORM HEIGHT/ROAD CLEARANCE	22"/6" LOADED (ADJUSTABLE)
CROSSMEMBER SPACING	ON 20" CENTERS
AUXILIARY CROSSMEMBERS	OUTSIDE OF MAINBEAMS BETWEEN CROSSMEMBERS
FRONT FOLDING RAMPS	41" LONG-WOOD FILLED-ADJUSTABLE, SPRING ASSIST
FRAME REINFORCEMENT	FOR 4 CLOSED COUPLE AXLES ONLY
SPECIAL BUCKET TROUGH	69" FORWARD OF SLOPE AND CLEAR THROUGH TO 1ST AXLE (REF Q32880)
HYDRAULIC SYSTEM	FROM TRACTOR WETLINE
GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT
GOOSENECK SUPPORT CYLINDER	HYDRAULIC
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/ VERTICAL AIR LOCK PIN
SWING CLEARANCE	108" & 84"
FIFTH WHEEL HEIGHT (50" LOADED)	48"-50"-52"-54"-56" LOADED (ADJUSTABLE)
1/8" ALUMINUM TOP COVER	OVER GOOSENECK AREA
AIR BRAKES	16.5" X 7" W/ AUTO SLACKS & OUTBOARD DRUMS
ANTI-LOCK BRAKES	NONE (TRAILER GVWR EXCEEDS 120,000#)
SPRING BRAKES	ON 2ND AXLE
AXLES	(3) 25,000# 3/4" WALL W/ 23,000# BRAKES AND LIMIT CHAINS
TIRES	(12) 275/70R22.5 (H)
WHEELS	ACCURIDE EXTRA POLISHED OUTERS, STEEL DISC INNERS
SUSPENSION	AIR RIDE W/ 50" AXLE SPACING
SUSPENSION	AIR LIFT 3RD AXLE ONLY
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL
RAISING AND LOWERING VALVE	AT REAR OF TRAILER
LIGHTS	L.E.D. RUBBER SEALED SYSTEM
BATTERY BACK-UP	AMBER STROBE LIGHTS ON BATTERY-BACK UP
3RD TAILLIGHT PACKAGE	AMBER L.E.D. STROBE WARNING LAMPS
LASH RINGS	(18) TOTAL- 6-PER SIDE (BENT STYLE), 1-EACH SIDE FRONT OF DECK FLAT STYLE ON 45 DEGREE ANGLE, 1-EACH BOLSTER END (FLAT STYLE)
EXTENSION BRACKETS (OUTIGGERS)	12" SWINGING/REMOVABLE OUTRIGGERS (WITHOUT PLANKS); INCLUDES 12" DOUBLE HOOK-ON OUTRIGGERS AT FRONT OF DECK. "FULL LENGTH" OF DECK
DECKING	1-1/2" APITONG FULL WIDTH
PAINT	GLOSS BLACK (2-PART URETHANE) STEEL PARTS TO MATCH PAINT COLOR



	,
FLAG HOLDER SLOTS	IN BOLSTERS
REAR DECK	OPEN BOOMWELL WITH EXTRA LOW FIRST CROSSMEMBER AND WITH 1 1/2" APITONG OVER TIRES ONLY (NO COVER PLATE)
REAR SLOPE (MAIN TO REAR DECK)	3 TO 1 (18 DEGREE) W/ OPEN CENTER
ROLLER STOP AT REAR	4" HIGH, WIDTH OF MAIN BEAMS
FLAG HOLDER W/ THUMB SCREWS	1-PAIR FRONT CORNER OF DECK, 1-PAIR ENDS OF LIGHT PANEL
AIR AND ELECTRICAL CONNECTIONS	FOR FUTURE FLIP/REMOVABLE AXLE
ALUMINUM STORAGE BASKET BOLT-IN	(1) AT FRONT OF DECK

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed