

# HALE

## TRAILER

### BRAKE & WHEEL



**A032446-A032447**  
**VIN: A6869-A6870**

#### SALES | RENTALS | PARTS | SERVICE

|                   |              |                  |              |
|-------------------|--------------|------------------|--------------|
| Allentown, PA:    | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD:    | 888-601-7500 | Portland, ME:    | 800-325-4253 |
| Concord, NC:      | 800-438-2250 | Raleigh, NC:     | 833-418-9777 |
| Delmar, DE:       | 866-486-1400 | Scranton, PA:    | 800-569-1400 |
| Des Moines, IA:   | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD:       | 800-544-7127 | Voorhees, NJ:    | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA:     | 800-854-5310 |

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

| Rear Axle 60-90 Only available in 60" spread (Model: MAG FA 6090 60)  |                         |
|---|-------------------------|
| AXM609060RS   | Est. Wt.: 3,270# +/- 3% |
| TRAILER - GENERAL   |                         |
| <b>Compatibility:</b> Magnitude 60HD, 65, 75 and 80 ton <b>Attach to A6861-A6862</b>  |                         |
| <b>Width:</b> 8 feet 6 inches   |                         |
| AXLES   |                         |
| <b>Number of Axles:</b> 1 axle  |                         |
| <b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle <b>NOTE: GAWR determined by suspension type, brakes, tires and other components.</b> |                         |
| <b>Axle Spread:</b> 60 inches (between axles)   |                         |
| <b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount                                      |                         |
| <b>Dust Shields on Flip Axle:</b> None  |                         |
| SUSPENSION  |                         |
| <b>Suspension:</b> Air ride   |                         |
| WHEELS AND TIRES  |                         |
| <b>Wheels:</b> 8.25 x 22.5 Outer <b>LvL One buffed/steel disc inside - hub-piloted</b>  |                         |
| <b>Tires:</b> 275/70R 22.5 OEM Standard   |                         |
| <b>Tire Inflation:</b> Tire Inflation Installed   |                         |
| REAR BRIDGE   |                         |
| <b>Boom Trough:</b> V-style boom trough with bolt-in V pan  |                         |
| <b>Manual Dump Valve:</b> Manual Dump Valve (Push Pull)   |                         |
| <b>Bumper:</b> Heavy duty V-style rear bumper   |                         |
| <b>Accent Package:</b> None   |                         |
| LIGHTING  |                         |
| <b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted amber strobes                                    |                         |
| PAINT   |                         |
| <b>Paint:</b> Fontaine black polyurethane enamel PN 51172000/G02BC0001  |                         |
| MISCELLANEOUS   |                         |
| <b>Lash Rings:</b> 1 pair - 2 total   |                         |
| <b>Flag Holders:</b> Flag holders - 1 pair located on rear bumper   |                         |
| <b>VIN Plate:</b> Bilingual VIN plate   |                         |

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.