



A032507-A032508 VIN: S031372-S031373

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: Raleigh, NC 833-418-9777 800-438-2250 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Springfield, MA: Des Moines, IA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: Walpole, MA: 800-828-3055 800-854-5310

XL 130 Hydraulic Detachable Gooseneck

OVERALL LENGTH 54' 10'
OVERALL WIDTH 102"

CAPACITY 130,000 LB DISTRIBUTED; 130,000 LB IN 10'

WEIGHT +/- 3% 0,000 LB

GOOSENECK

 NECK STYLE
 CLASSIC NECK

 LENGTH
 12' 10"

 KINGPIN SETTING
 16"
 40"

 SWING CLEARANCE
 110"
 86"

5TH WHEEL HEIGHT 49" W/ 7 VARIABLE RIDE HEIGHT POSITIONS

HYDRAULICS RUNS OFF WET KIT (5 TO 12 GPM HYD. REQUIREMENTS)

FLIP NECK PREP FOR 72" FLIP NECK

TOOLBOX IN REAR OF GOOSENECK W/ ALUMINUM DOOR (INCLUDES PROTECTOR PLATE/CHAIN RACK

MAIN DECK

LENGTH 28'

LOADED DECK HEIGHT 23" W/ 6" GROUND CLEARANCE

DROP SIDE OUTSIDE BEAMS (14-1/2" DECK HEIGHT- 6" GROUND CLEARANCE)

DECKING 1 3/4" APITONG DECKING, RAISED - CENTER OPEN

CROSSMEMBER HEAVY 4" & 4" STUBBED JR I-BEAM 12" ALTERNATING CENTERS

BEAMS (2) 17" FAB I-BEAMS; (2) BEAMS 8 1/2"

TOP FLANGE REINFORCEMENT, FRONT RAMP AND MAIN DECK

D-RINGS (8) BENT D-RINGS PER SIDE

OUTRIGGERS REMOVABLE H.D. SWING OUT OUTRIGGERS - 24" CENTERS, CENTER SWINGS TOGETHER

PULLOUT FRONT H.D. OUTRIGGER

CHAIN DROPS 24" CENTERS - OUTSIDE BEAMS

REAR DECK

LENGTH 14' WITH 32° REAR TRANSITION

LOADED DECK HEIGHT 43

 AXLES
 (3) 25,000 LBS. NOMINAL (3/4" WALL)

 SUSPENSION
 HENDRICKSON / 30,000 CAPACITY / AIR RIDE

AXLE SPACING 54 1/2"

ABS NA SPRING BRAKES ON (1) AXLE

TIRES 275 / 70R / 22.5 (J)

WHEELS 8.25 X 22.5 10-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE, STEEL INSIDE DISC

BRAKES 16 1/2" X 7"; 25K

DRUMS OUTBOARD - SEVERE DUTY HUBS

ELECTRICAL 12V SEALED GROTE SYSTEM WITH (3) TAIL LIGHT ALUMINUM PACKAGE

4" AMBER STROBE TO BE USED AS 3RD TAIL LIGHT

BATTERY BACKUP

4-WAY PLUG AT REAR TO RUN BATTERY BACKUP FOR STROBE

 DECKING
 OPEN WHEELS BOLSTER STYLE, OPEN BOOM TROUGH

 D-RINGS
 (1) PAIR FLAT D-RINGS ON MAIN BEAMS AT FRONT

(1) PAIR FLAT D-RINGS ON MAIN BEAMS AT REAR (2) PAIR FLAT D-RINGS IN BOOM TROUGH CHAIN DROPS (2) CHAIN DROPS PER BOLSTER
STAKE POCKETS (2) STAKE POCKETS AT REAR

PAINT GALVANIZED: PAINTED WEBS

GALVANIZED: MAIN DECK, WHEEL AREA

PAINTED BLACK: GOOSENECK, OTHER REMOVABLE COMPONENTS

ADDITIONAL MANUAL RIDE HEIGHT CONTROL

COLAS+ RAISE AND LOWER VALVE
PREP FOR A TWO AXLE POWER BOOSTER
PREP FOR FLUSH MOUNT FLIP AXLE

AIR LOCK FLIP AXLE PINS

LIQUID FILLED AIR GAUGE

BUCKET WELL AT REAR OF MAIN DECK WITH PLATE ON BOTTOM WITH (4) FLAT D-RINGS

TOOLBOX AT FRONT OF MAIN DECK WITH (4) FLAT D-RINGS

(2) PAIR EZ MOUNT FLAG HOLDERS AIR LIFT AXLE ON 3RD AXLE

(2) ADDITIONAL CLEARANCE LIGHTS PER SIDE ON MAIN DECK