



A032595-A032596

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

f

🐦

in

📷

📺

800-232-6535

*FINANCING AVAILABLE



Fifth wheel height : 51"

Gooseneck: ☒ Fix

King Pin Location

☒ 16" ☒ Bolt on

Fifth Wheel:

☒ Sliding

Hydraulic Hose:

☒ No

13 HP Honda Power Pack:

☒ Yes

Coupler :

☒ 1/4" HTS

Plate

Frame :

☒ Other : tapered

Top flange :

☒ Other:

BTM Flange :

☒ Other:

X-Members:

8" "I" beams at 13 lbs../ft

Front fenders :

☒ No

Rear fenders:

☒ Yes

D-Rings:

☒ Yes (6) ☒ to lift

Bumper :

☐ Straight ☒ short

Mud flaps :

☒ Témisko

Location :

removable at rear

Lights :

☒ Truck-lite round type (2/s) ☒ Other : LED

Dolly :

☒ Holland ☒ Double Crank : ☒ R/S

Ladder:

☒ No

Jeep dolly

Length : 33 ft 8in Width : 120

Axles : 2 ☒ 3

Suspension : ☒ Hendrix. HT-250U

☒ Scale-O-Matic ☒ Ball valve ☒ Manual ride height adj. Valve ☒ Chains on axle

Axle location: 24"-60"-60"

Removable axle : ☒ No

Axle track : 77.5"

Axles : ☒ F24 - 25.000 lbs. For 22.5wheels

Seals : Stemco Guardian HP Bearings : Stemco

Brake chambers: ☒ Maxi 30/30T

Automatic Slack adjuster : ☒ Haldex

Brake valve : Rockwell Wabco

Brake lining : ☒ 16 1/2 x 7 x 3/4 Q ☒ CM 20

Hubs : ☒ Dura Light 10 studs steel piloted hubs

Drum : ☒ Cast

Rims : Qty : 12 ☒ Alum ☒ Aluminium LVL ☒ 22.5 x 8.25

☒ Plastic spacer (rim & rim) ☒ Plastic spacer (hub & rim)

Tires : Qty : 12 ☒ 16 Ply Model : Size : 275/70R22.5

Hubodometer : ☒ no Location :

Title holder : Location : On neck ☒ Truck-lite

Paint : Color: Black ☐ Color code #: ☒ Metalized

Gladhand storage in neck

Spare tire rack on top of neck