

HALE TRAILER BRAKE & WHEEL



A032616-A032618
VIN: S031479-S031481

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Fusion Drop Deck 48' Tridem Air Ride (Model Code: HAFGD12TAF)

Length / Width: 48 feet x 102 inches

Suspension Type: Tri-axle air

Deck Lengths: 10 feet front and 38 feet rear

Frame Rating: 100,000 lbs distributed - GAWR and tire ratings determine legal payloads

Rear Deck Height: 40 inches - loaded

Flooring: 1/8 inch wood

Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel Galvanized

Single Coil Hauling Package: Included

Side Rails: Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

Rubrail: Integrated with siderail

Main Beams: 130K load bearing flanges - Galvanized

Kingpin: 18 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM Standard Painted Black

Knee Braces: Fabricated on approx. 60 inch C/C - Galvanized

Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front

Bulkheads: None standard

Number of Axles: 3

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed

ABS: Meritor Wabco iABS 4S/2M - no cable or tool

Axle Spread: 61 inches, 61 inches - set at rear (*Approx. 38' 11" C/L KP to C/L Tridem)

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 6 steel disc inside wheels - 6 aluminum High Polish outside with 6 Spacers

Tires: 255/70R 22.5 16PR OEM standard

Tire Inflation System: Hendrickson TIREMAAX PRO inflation system

Suspension Detail: Hendrickson AANL23K Intraax air ride Painted Black

Auto Glad Hand Dump : Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Air Lift: (1) UBL installed on Rear Axle; Includes additional leveling valve to fully raise lower deck when this axle is lifted to try and achieve additional tire ground clearance; NOTE: LOAD ON 2 AXLES NOT TO EXCEED 20K EACH; FONTAINE WILL NOT BE RESPONSIBLE FOR TIRE FLAT SPOT AND/OR DAMAGE DUE TO REAR LIFTED AXLE.

Air Tank: Aluminum Air Tanks Installed

Front Corners: Tapered

Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD

Paint: Galvanized Frame with Fontaine Fusion Decals

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails

Bumper: Weld-on type - meets underride requirements

Mudflaps: 1 set OEM standard behind rear axle

Winch Track: Full length integrated double L type aluminum on both sides where possible -- STANDARD

Sliding Winches: 12 total, 2 front deck and 10 rear deck: 6 each side **ZINC**; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD

27 foot Winch Straps: None standard

30 foot Winch Straps: None standard

Dock Bumpers: 1 pair rubber on rear

Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.