

HALE

TRAILER

BRAKE & WHEEL



A032645-A032649
VIN: 25574, 25576-25579

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

XL 55 MFG

OVERALL LENGTH	53'
OVERALL WIDTH	102"
CAPACITY	55,000 LB DISTRIBUTED, 55,000 IN 20'
WEIGHT +/- 3%	0,000 LB
GOOSENECK	
LENGTH	9' 6" FULL-WIDTH NECK PERIMETER FRAME STYLE (FULL WIDTH)
KINGPIN SETTING	16"
SWING CLEARANCE	87"
	PLUMB CONNECTIONS ON INSIDE OF GOOSENECK
5TH WHEEL HEIGHT	50" - CUSTOMER TO CONFIRM
	5TH WHEEL PLATE TO SIT 2" LOWER THAN GOOSENECK BEAM BOTTOM FLANGE
	SHIMMABLE NECK - SHIMS INCLUDED
	QUICK COUPLER ON FRONT OF MAIN DECK
DECKING	1 1/8" APITONG DECKING FLUSH
D-RINGS	(2) PAIR OF PAN STYLE D-RINGS - (1) EACH CORNER
	NO BENT D-RINGS PER SIDE
MAIN DECK	
LENGTH	35'
	90" INSIDE TO INSIDE DIMENSION NEEDED
LOADED DECK HEIGHT	16" W 4" GROUND CLEARANCE
	1/4" WEAR PLATE FULL LENGTH ON BEAMS WITH KICK UP AT FRONT OF THE DECK
	1/4" WEAR PLATES DOWN CENTER OF TRAILER, FULL LENGTH
	5" HEIGHT TO TOP OF PLATE AND 7" LOADED HEIGHT TO TOP OF CROSSMEMBERS
DECKING	3/16" PLATE UNDER CROSSMEMBERS
CROSSMEMBER	FABRICATED CROSSMEMBERS ON 24" CENTERS - 2" X 2"
	OUTSIDE WEB STIFFENERS WITH 3" X 1/4" RUBRAIL
SIDE BEAMS	2 PERIMETER FRAME BEAMS - 12"
D-RINGS	FLAT D-RINGS ON INSIDE OF BEAMS - 24" CENTERS
REAR DECK	
LENGTH	8' 6"
LOADED DECK HEIGHT	38"
AXLES	(2) 25,000 LBS. NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	49"
ABS	4S2M WITH SPRING BRAKES ON (2) AXLES
TIRES	245 / 70R / 17.5 MICHELIN
WHEELS	6.75 X 17.5 8-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE, MILLED ALUMINUM INSIDE DISC
BRAKES	12 1/4" X 7 1/2"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH (3L +5L + 3L) DUAL INTENSITY TAIL LIGHT ALUMINUM PACKAGE
	4" AMBER STROBE IN THE 4TH AND 8TH POSITION. 4" TURN AND MARKER IN 1ST AND 11TH POSITION
	4" STOP AND MARKER LIGHTS IN THE 2ND, 3RD, 5TH, 6TH, 7TH, 9TH AND 10TH POSITION
DECKING	1 1/8" APITONG DECKING FLUSH
D-RINGS	2 PAIR OF PAN STYLE D-RINGS - ONE (1) EACH CORNER
D-RINGS	(2) BENT D-RINGS IN TAIL CHANNEL
PAINT	
	ZINC RICH PRIMER
	BLACK
ADDITIONAL	
	RIDE HEIGHT SET AT 10" FOR 4" GROUND CLEARANCE
	TRIPLE DONUTS
	MANUAL RIDE HEIGHT CONTROL
	RAISE AND LOWER VALVE
	(11) TOTAL TRUCKLITE PENNY LIGHTS AND CONNECTORS PER SIDE
	(3) ON UPPER DECK, (6) ON MAIN DECK, (2) ON REAR DECK TRANSITION,
	AND (1) REAR CLEARANCE LIGHTS TO BE BEEHIVE LOOK)
	LOOM AROUND TRUCKLITE LIGHTS AND CONNECTORS
	LIGHTS AND WIRING ABOVE CROSSMEMBERS
	NYLON LIMIT STRAPS
	GREASE HUBS IN LIEU OF OIL
	GLADHAND DUMP VALVE

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.