



Hale Trailer Brake & Wheel 032957-032962

HYDRAULIC DETACHABLE GOOSENECK

MODEL	RTN55TD3-PS TRAILER
TONS CAPACITY	55 IN ANY 16'
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL
CUSTOM/PAVER SPECIAL	TAPERED FRONT BEAMS (8-3/8" DEEP)
PLATFORM WIDTH	8'-6"
PLATFORM LENGTH	24' (MUST HOLD 53' O.A.L.), NOT TO EXCEED 43'-0" FROM THE 84" KINGPIN TO THE CENTER OF THE 2ND AXLE
PLATFORM HEIGHT/ROAD CLEARANCE	22"/6"
CROSSMEMBER SPACING	ON 20" CENTERS
AUXILIARY CROSSMEMBERS	ON 10" CENTERS (OUTSIDE MAIN BEAMS)
FRONT FOLDING RAMPS	41" LONG-WOOD FILLED-ADJUSTABLE
FRAME REINFORCEMENT	FOR FUTURE 4TH CLOSE COUPLED AXLE
HYDRAULIC SYSTEM	FROM TRACTOR WET LINE
GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT
GOOSENECK SUPPORT CYLINDER	HYDRAULIC
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/VERTICAL AIR LOCK PIN
FIFTH WHEEL HEIGHT (50" LOADED)	48" -50" -52" -54" -56" LOADED (ADJUSTABLE)
SWING CLEARANCE	108" & 84" DUAL KING PIN SETTINGS
1/8" ALUMINUM TOP COVER	OVER GOOSENECK AREA
AIR BRAKES	16.5" X 7" W/AUTO SLACKS & OUTBOARD DRUMS
ANTI-LOCK BRAKES	NONE (TRAILER GVWR EXCEEDS 120,000#)
SPRING BRAKES	ON ONE AXLE
AXLES	(3) 25,000#, 3/4" WALL
TIRES	(12) 275/70R22.5 (H)
ALUMINUM WHEELS (POLISHED OUTERS)	& STEEL DISC INNERS, 10-HOLE, HUB PILOTED, 8.25" X 22.5"
SUSPENSION	RIDEWELL AIR RIDE W/50" AXLE SPACING
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL

MANUAL EXHAUST VALVE	ON ALL AXLES
AXLE AIR LIFT	ON 3RD AXLE
LIGHTS	L.E.D. TRUCK-LITE RUBBER SEALED SYSTEM
BATTERY BACK-UP	REAR WARNING LIGHTS WITH RECHARGABLE BATTERY FLASH ALL LIGHTS W/SWITCH FOR STROBES WHEN TRAVELING
3RD TAILLIGHT PACKAGE	AMBER L.E.D. STROBES FOR WARNING LAFAPS
AIR & ELECTRICAL	@REAR FOR FUTURE 4TH AXLE
LASH RINGS	(18) TOTAL- 6-PER SIDE (BENT STYLE), 1 PER SIDE AT A 45° ANGLE AT FRONT OF DECK (FLAT STYLE), 1-EACH BOLSTER END (FLAT STYLE)
EXTENSION BRACKETS (OUTRIGGERS)	12" SWINGING/REMOVABLE W/DBL HOOK-ON
DECKING	1-1 1/2" APITONG-FULL WIDTH
PAINT	GLOSS BLACK(2-PART URETHANE)
CHAIN HOOK & FLAG HOLDER SLOTS	ON BOLSTERS
STORAGE BASKET	(1) 2ND SECTION FROM FRONT
REAR DECK	OPEN BOOMWELL W/ 1-1/2" APITONG OVER TIRES ONLY
SPECIAL BUCKET TROUGH	40" FORWARD OF SLOPE AND CLEAR THROUGH TO 1ST AXLE
REAR SLOPE (MAIN TO REAR DECK)	21 DEGREE WOOD FILLED (OPEN CENTER)
ROLLER STOP@REAR	4" HIGH, WIDTH OF MAIN BEAMS
PIPE TYPE FLAG HOLDER W/ TUMB SCREWS	(1) PAIR AT FRONT OF DECK, (1) PAIR AT REAR OF TRAILER

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.