



Hale Trailer Brake & Wheel 032965-032966

HYDRAULI DETACHABLE GOOSENECK	
MODEL	R1N35TD-PS TRAILER
TONS CAPACIY	35 TONS IN ANY 16'
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL
CUSTOM/PAVER SPECIAL	TAPERED FRONT BEAMS (8-3/8" DEEP)
PLATFORM WIDTH	8'-6"
PLATFORM LENGTH	23'
PLATFORM HEIGHT/ROAD CLEARANCE	22"/6"
FRONT FOLDING RAMPS	41" LONG-WOOD FILLED-ADJUSTABLE
CROSSMEMBER SPACING	ON 20" CENTERS
HYDRAULIC SYSTEM	FROM TRACTOR WET LINE
GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT
GOOSENECK SUPPORT CYLINDER	HYDRAULIC
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/VERTICAL AIR LOCK PIN
SWING CLEARANCE	90"
FIFTH WHEEL HEIGHT	48"-50"-52"-54"-56" LOADED (ADJUSTABLE)
118" ALUMINUM TOP COVER	OVER GOOSENECK AREA
AIR BRAKES	16.5" X 7" W/AUTO SLACKS & OUTBOARD DRUMS
ANTI-LOCK BRAKES	2S/2M SYSTEM (2-SENSORS/2-MODULATORS)
SPRING BRAKES	ON ONE AXLE
AXLES	(2) 22,500# 5/8" WALL
TIRES	(8) 255/70R 22.5 (H)
ALUMINUM WHEELS (POLISHED OUTERS)	& STEEL DISC INNERS, 10-HOLE, HUB PILOTED, 8.25" X 22.5"
SUSPENSION	RIDEWELL AIR RIDE W/55" AXLE SPACING
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL
MANUAL EXHAUST VALVE	ON ALL AXLES
LIGHTS	L.E.D. TRUCK-LITE RUBBER SEALED SYSTEM

BATTERY BACK-UP	REAR WARNING LIGHTS WITH RECHARGABLE BATTERY FLASH ALL LIGHTS
3RD TAILLIGHT PACKAGE	NUMBER FOR WARNING LIGHTS
LASH RINGS	(12) TOTAL- 4 PER SIDE (BENT STYLE), 1 PER SIDE AT A 45° ANGLE AT FRONT OF DECK (FLAT STYLE), 1 EACH BOLSTER (FLAT STYLE)
EXTENSION BRACKETS (OUTRIGGERS)	12" SWINGING/REMOVABLE W/DBL HOOK-ON INFRONT
DECKING	1-1/2" APITONG-FULL WIDTH
PAINT	GLOSS BLACK (2-PART URETHANE)
CHAIN HOOK & FLAG HOLDER SLOTS	ON BOLSTERS
STORAGE BASKET	(1) 2ND SECTION FROM FRONT OF DECK
REAR DECK	FULL WIDTH-WOOD COVERD, 1-1/2" APITONG
REAR SLOPE (MAIN TO REAR DECK)	3:1 18 DEGREE FULL WIDTH WOOD FILLED
ROLLER STOP@REAR	4" HIGH, WIDTH OF MAIN BEAMS
PIPE TYPE FLAG HOLDER W/ THUMB SCREW	(1) PAIR AT FRONT OF DECK, (1) PAIR AT REAR OF TRAILER

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.