



A033008-A033013 VIN: 48412-48417

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 833-418-9777 800-438-2250 Raleigh, NC Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: Springfield, MA: 800-854-5306 888-673-5011 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

Base Model #: DF48 x 102 60 Ton 275 Tires Serial #: 48412 - 48417

components description

CAPACITY Heavy Duty Package - 120,000 lbs. GVWR (110K Eq. Dist. & 90,000 in 10' Span)

OVERALL LENGTH 48'

UPPER DECK LENGTH 12'

* * * Minimum Pitch of 2-3/4" * * *

LOWER DECK LENGTH 36' (Deck Height-42")

OVERALL WIDTH 8'6"

KING PIN SETTING 18"

UPPER COUPLER PLATE 5/16"

UPPER COUPLER HEIGHT * * 50" * *

BULKHEAD None

MAINFRAME 26" Fabricated - PreCambered I-Beams - Heavy Duty

* * Main Beams 1/2" X 5" Top Flange, 3/4" x 5" Bottom, 1/4" Webs Throughout, Lower Deck, 1/4 Rear

Section, 1/4" Web in Neck. * *

* * Transition Plate * *

* * 1/4" Diamond Plate Over Wheels. * *

* * * 1/4" Diagonal Bracing, Main Beam to Outer Rail. * * *

* * * * Rear of Trailer Prep for 4th Flip Axle. * * * *

SIDE RAILS 8" Heavy Duty

FLOOR SILLS 6" I-Beam 12/12/12 O.C. HD Pkg. Drop Frame

* * Approx. 6 Aux. Crossmembers over Suspension at Middle of Trailer, and in Gooseneck. * *

* * Install Sub Sills in High Stress Areas. * *

FLOOR DECKING * * 1-1/2" Apitong * *

WINCH TRACK Steel Slide Entire Length of Drivers Side

WINCHES 12

STRAPS None

LANDING GEAR Two Speed

SUSPENSIONS (Hendrickson)- 30K Suspension W/ (30K) Lift Rear Axle

9" Ride Height.

LIFT AXLE Lift Rear Axle

DUMP VALVE Dump Valve in Box Includes: Manual Override, Liquid Filled Gauges and Lift Axles

** All Air Control valve in Box.**

SCALES None

AXLES (3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride(Parallel Spindle)

Parallel Spindle.

23K Brake Linings.

AXLE SPACING 61" Wide Spread

PARKING BRAKES 3 Axle

DUST SHEILDS None

WHEELS Disc - Hub Piloted - Steel Inside and Polished Aluminum Outer

* * * * Steel Inside, Polished Outside w/ Wheel Pads Between Wheels * * * *

TIRES 275/70R 22.5 - 42" Loaded Deck Height

Double Coin.

ANTI-SAIL MUD FLAPS Rear Frame
STAKE POCKETS 4" Deep - 24" O.C. - Sides Only
RUB BAND STEEL 3/8" X 3"
PIPE SPOOLS Double
DOCK BUMPERS None
**** Heavy Duty Rear Skirt and Rear End Material ****
*** Aluminum Sheet on Outside Rear to Cover 3 Light Stop/Tail/Turn ***
LIGHTS Sealed Wiring Harness w/ LED Pkg
Use Flange Mounted Anti-Theft S/T/T On Rear Skirt, (Due To Skirt Thickness).
PAINT Black - SWP Epoxy Primer and Acrylic Polyurethane - Shot Blasted
CUSTOM 1. Strobe Kit- 3-3-3 Toggle Switch - D/S - Rear Trailer
CUSTOM 2. Grote Document Holder Landing Gear R/S
CUSTOM 3. Heavy Duty Decals
Reference #: 45066