

BASE MODEL: DC-48 | Drop Deck Combo Flatbed

Standard

CAPACITY Beam Pkg - 80,000 GVWR (60,000 in 10'Span)

OVERALL LENGTH 48'
UPPER DECK LENGTH 10'
LOWER DECK LENGTH 38'
OVERALL WIDTH 8' 6"

KING PIN SETTING 18" Squared Front

UPPER COUPLER PLATE
UPPER COUPLER HEIGHT
FRONT SKIRT
REAR SKIRT
Aluminum
BULKHEAD
None

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)
SIDE RAILS 6"-Alum-Extruded W/Double L Track

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.
LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer

FLOOR DECKING 1-1/8" HD Aluminum W/4 Nailer Boards

WINCHES 12 DOUBLE L

WINCH TRACK Double L Aluminum - Extruded Siderail Both Sides

STRAPS None
LANDING GEAR Two Speed
SUSPENSIONS Air Ride– 2 Axle

SUSPENSION LOCATION King Pin to Center of Rear Axle 43'

AXLES (2) 22.5K Cap.- Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires

AXLE SPACING 10'2" Wide Spread

LIFT AXLE None

DUMP VALVE Electric Wired to Front

SCALES None
PARKING BRAKES All Axles

ABS SYSTEM ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Piloted - 22.5 – All Steel

TIRES 255/70R 22.5 Tires 41" Loaded Deck Height

TIRE INFLATION SYSTEM None

ANTI-SAIL MUD FLAPS Behind 2 Axles

STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear

PIPE SPOOLS Double

RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape

DOCK BUMPERS Rubber Inboard

CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced

CONTAINER TWIST LOCKS None
TIRE CARRIERS DUNNAGE None
RACK None

TOOLBOX TYPE
TOOLBOX LOCATION

LIGHTS TBD

CUSTOM LIGHTS Sealed Wiring Harness w/ LED Pkg

PAINT

CUSTOM 1. None
CUSTOM 2. Black
CUSTOM 3. None
None

None DISCLAIMER