

HALE

TRAILER

BRAKE & WHEEL



A033315-A033321

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Infinity Drop Deck 53 Rear Axle Slide (HAICD22RSA)

Detailed Specifications		General	
Model	HAICD22RSA		
Length x Width	53 feet x 102 inches		
Deck Length	11 feet Front and 42 feet Rear		
Rear Deck Height	40 inches Loaded		
Suspension	Rear Axle Slide		
Frame Rating	80,000 lbs Distributed - 55,000 lbs Concentrated in 4 feet- GAWR and Tire Ratings Determine Legal Payloads		
Kingpin Setting	30 inches		
Fifth Wheel Height	49 inches		
Axle Spread	122 inches Open - 61 inches Closed; Meets California, Canadian RTAC and BC Dimensional Specifications in Closed Position		
VIN Plate	Bilingual US/Canadian VIN plate		
Estimated Weight	Est. Weight: 11501 lbs. +/-3%		
Structural			
Main Beams	130K Load Bearing Flanges		
Crossmembers	18 inch Centers Front Deck / 12 inch Centers Rear Deck - 4 inch Jr. I-Steel		
Single Coil Hauling Package	Included		
Knee Braces	Fabricated on Approx. 60 inch C/C		
Side Rails	Exclusive Revolutionary RASR Rail Technology - One Piece Routed Aluminum Designed for Strength and Impact		
Stake Pockets	Routed Aluminum on 24-inch Centers (2 Load Securement Openings in Between Stake Pockets)		
Rubrail	Integrated with Side Rail		
Front Corners	Tapered Steel		
Bumper	Weld-On; Meets U.S. Underride Requirements - Painted Steel		
Winch Track	Full-Length Integrated Double L Type Aluminum on Both Sides Where Possible		
Chain Cargo Tie Downs	17 Pair - Recessed in Siderails		
Bulkhead Pockets	4 - DOT Type Bulkhead Pockets Only - Welded to Front		
Landing Gear			
Landing Gear	Jost A400G19 Steel Landing Gear		
Flooring			
Flooring	1 1/8 inch Aluminum with 4 Apitong Wood Nailer Strips		
Suspension			
Suspension Detail	Hendrickson AANL23K and AAZL23K Buttoned-Up Intraax Air Ride		
Number of Axles	2		
Axle Spindle	Tapered		
Brakes	Spring Brakes, Auto Slacks		
Hubs and Drums	10-Hole Hub-Piloted with Outboard Cast Drums		
Wheel Ends	Grease in Hubs - *** 5-Year Wheel End Warranty ***		
Tire Inflation System	None Standard		
Air Lift	None Standard		
Wheels and Tires			
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-Painted White - STANDARD		
Tires	255/70R 22.5 16PR OEM Standard tires		



Detailed Specifications

Air System

Air Line Filters	(2) Meritor In-line Type Installed
ABS	4S/2M - No Cable or Tool
Full System Dump	Auto Glad Hand Dump Installed
Electric Dump Valve	Wired to 7-Way Auxiliary Socket to Dump Rear Axle
Control Box	Standard Mount of Controls on Slider Frame
Gladhand Position	Front Gladhands and Electrical Connections in Center of Trailer

Electrical System

Tailskirt Lights	LED: 2 Lights/Side on Rear
Side Marker Lights	LED: 3 Lights/Side

Paint and Decal

Paint	Black Urethane on Steel Parts with Infinity Decals
Conspicuity Tape	Per NHTSA Specs - Installed in Recess on Rubrails
Unit Number & Decals	Fontaine Standard Decals Installed

Miscellaneous

Mudflaps	2 Sets OEM Standard; Spring Loaded Brackets Behind Front Axle
Sliding Winches	12 standard: 2 Top Deck - 10 Lower Deck; Sliding Rope Hook/Winch Strap Hook Retainers
Winch Location	Equal Both Sides
27' Winch Straps	None Standard
30' Winch Straps	None Standard
Dock Bumpers	1 Pair Rubber on Rear
Sliding J-Hook for Strap with Ring	None Standard
Registration Holder	Install Registration Holder - OEM Standard

Options

Bulkhead	None Standard
Spare Tire Carrier	1 Standard - Mounted Between Lower Gooseneck Beams at Drop
Hubodometer	None Standard
Tool Box	None Standard

Literature

Trailer Literature	Infinity Brochure
--------------------	-----------------------------------

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.