

# HALE

## TRAILER

### BRAKE & WHEEL



A033322-A033327

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

GVWR: 90,000#

Beam Rating in 10': 60,000#

#### FRAME

Type	Drop Deck		
Model	Titanium		
Neck Type	Fixed Gooseneck - Full Width		
Extendible	None		
Length		Feet	Inches
	Overall length	53	0
	Top deck length	11	0
	Bottom deck length	42	0
	Well length		
Width	102 Inches		
Beams	2 Main Beams (Standard on 43" Beam Centers)		
Inner Beam Flange	Aluminum: 1" x 5" Top Flange & 1 .05" x 6" Bottom Flange (Heavy&Super Duty)		
Web Thickness	Aluminum: 0.380" Thickness (Heavy Duty & Super Duty Beams)		
Inner Beam Depth	25" - Titanium Heavy Duty Beam - Huck Bolted Construction		
Beam Holes	None		
Well Deck Height	No Well with a Flatbed or Dropdeck Trailer or Flip Axle		
Sill Height	Aluminum: 5" Crossmember Height on 12" Centers.	12" Lower deck - 18" Top deck	
Coil Kit	One Coil Kit - 7 Aluminum Stub Sills		
Rear Deck Height	41 Inches - Dropdeck (Plat/Chap/Titanium - Based on 22.5" Tires)		
Fifth Wheel Height	49 Inches		
King Pin	30 Inches		
Side Rail	Aluminum: 7.4" Ext w/ J-Hook Track and Heavy Duty Continuous Contact Rub Rail		
Extra Stake Pockets	None	Pair Qty	0
Conspicuity Tape	Conspicuity Tape on Side Rail		
Front & Rear Plates	FRONT: Alum Bev Cnr NO-Stake Pkts - REAR: Alum NO-Stake Pkts & Rubrail		
Flag Holders	None		

<b>Rubber Dock Bumpers</b>	Rubber Dock Bumpers on Rear Sill	
<b>Drop Plate</b>	23" Aluminum Drop Plate (Chap on 22.5")	
<b>Knee Braces</b>	None.	
<b>Paint</b>	Aluminum Trailer: Susp & Axles are Undercoated, LG/FW painted Silver	
<b>Flooring</b>	Aluminum Floor W/ 3 Apitong Nailers	
<b>Load Hook Flooring</b>	No Load Hook Track in Floor	
<b>Landing Gear</b>	Jost AX150 Aluminum (10 Year Warranty, 5 Year No Lube) - Handle: Road	
<b>Rear Enclosure</b>	Open Aluminum Rearend - Lights In Rear Sill	
<b>PERIMETER BEAM OPTIONS</b>	<b>No Options Selected - Perimeter Beam Options May be Grouped</b>	
<b>OILFIELD OPTIONS</b>	<b>No Options Selected - Oilfield Options May be Grouped</b>	
<b>STRUCTURAL OPTIONS</b>	<b>No Options Selected - Structural Options May be Grouped</b>	
<b>SUSPENSIONS &amp; AXLES</b>	<b>GAWR: 20,280 #</b>	<b>2</b>
<b>Suspension Type</b>	Air Ride Suspension - Hendrickson -- AA230 (Intraax)	<b>Axles on this Configuration</b>
<b>Axle Type</b>	Hendrickson 23k Integrated RTR Axle - HXL5	
<b>Number of Axles</b>	2 Axles - Standard	Will have holes in main beams for slider pins so can easily be monitored
<b>Sliding Axles</b>	Dropdeck - Rear Axle Slide - Pins Through Internal Slider Tube	
<b>Axle Spacing</b>	61/122 Inches - For Rear Slider	Inches <input type="text" value="0"/>
<b>Overhang</b>	Determined by California Legal - Min. Overhang Est.: 63 Inche	Inches <input type="text" value="0"/>
<b>Cal &amp; Can Legal</b>	California Legal	
<b>Steerable Axle</b>	None	
<b>Lift Kits</b>	None	
<b>Axle Straps</b>	None	
<b>Axle Spindle Type</b>	N-Type (All Axles)	
<b>Brake Type</b>	Drum Brakes - Spring brakes with auto slack adjusters	
<b>Hub Type</b>	Cast - Hub Piloted	
<b>Drum Type</b>	Cast	
<b>Brake Dust Covers</b>	None	
<b>Bearing Lubricant</b>	Synthetic Semi Fluid Solid Grease	
<b>Hub-O-Meter</b>	None	
<b>Inflation Sys &amp; Crossfires</b>	None	
<b>Mudflaps</b>	One Pair Per Axle	
<b>TIRES &amp; WHEELS</b>		<b>8 Wheels and Tires in this Configuration</b>
<b>Tires</b>	Gladiator (Tier 3) 255/70R22.5 (H) - QR40ST - 120PSI	
<b>Outer Wheels</b>	22.5" Standard Duty Steel - White	

Inner Wheels

22.5" Standard Duty Steel - White

Spare Tire

None

Spare Wheel

None

Tire Carrier

None

LIGHTS

Rear Lights

3-3-3 Light Pattern - Center 3 are MicroDot Lights, Outers are 4" LED

Extra Row of Rear Light

None

Back-up Lights

None

Strobe Lights

None

Over Dimension Lights

None

Pair Qty

0

Side Marker Lights

MicroDot Lights - Qty between 4 and 9 Pairs

Pair Qty

5

Side Light Options

None

AIR & ELECTRICAL OPTIONS

Anti-lock Braking System

Meritor 4S/2M

Air & Electrical Connection

Standard Plus Extra 7-way in Front Plate with Harness PLUS 4-way in rear panel

Air Raise & Lower Valve

Air Raise & Lower Valve In An Aluminum Box (Mounted on Bracket)

ISO Type Aux 7 way on nose - Wired to Electric dump on rear axle

Dump Valve

Both Auto Dump & Electric Dump

Standard Steel air tank for air system

Pull Lanyards on Air Tanks

None

Electric dump on rear axle

Gauges And Scales

None

LOAD SECUREMENT

Winch Track

Winch Track (Double L) on Roadside & Curbside (Integrated in Aluminum Side Rail)

Tie Bar

Aluminum Tie Bar on Roadside & Curbside

Fixed Winches

None

Qty

0

Sliding Winches 1

Standard Sliding Winch - BLACK (Specify Qty)

Qty

12

[1 Ea side top, 5 ea side lower

Sliding Winches 2

None

Qty

0

Recessed Floor D-Rings

None

Pair Qty

0

Chain Ties

Recessed Chain Ties - Bolt-on (Specify Qty in Pairs in space to

Pair Qty

17

[

Rope Hooks

None

Pair Qty

0

C & G - Hooks

None

Qty

0

J-Hooks

None

Qty

0

J-Hook Carriers

None

Qty

0

Container Locks

None

Load Bunks

None

Qty

0

Bulkheads

None

No Options Selected - Box Options May be Grouped

BOXES

Tool Boxes: Type 1

None

Door: None

Locks: None

Qty

0

Tool Boxes: Type 2

None

Door: None

Locks: None

Qty

0

Gooseneck Boxes

None

Belly Boxes

None

Racks

None

DOVETAILS & RAMPS

No Options Selected - Dovetail Options May be Grouped

MISCELLANEOUS

Certificate Holder

Certificate Holders

FHWA Inspection

FHWA Inspection

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.