

HALE

TRAILER

BRAKE & WHEEL



A033328-A033333

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

GVWR: 90,000#

Beam Rating in 10': 60,000#

FRAME

Type	Drop Deck		
Model	Titanium		
Neck Type	Fixed Gooseneck - Full Width		
Extendible	None		
Length		Feet	Inches
	Overall length	53	0
	Top deck length	11	0
	Bottom deck length	42	0
	Well length		
Width	102 Inches		
Beams	2 Main Beams (Standard on 43" Beam Centers)		
Inner Beam Flange	Aluminum: 1" x 5" Top Flange & 1 .05" x 6" Bottom Flange (Heavy&Super Duty)		
Web Thickness	Aluminum: 0.380" Thickness (Heavy Duty & Super Duty Beams)		
Inner Beam Depth	25" - Titanium Heavy Duty Beam - Huck Bolted Construction		
Beam Holes	None		
Well Deck Height	No Well with a Flatbed or Dropdeck Trailer or Flip Axle		
Sill Height	Aluminum: 5" Crossmember Height on 12" Centers.	12" Lower deck - 18" Top deck	
Coil Kit	One Coil Kit - 7 Aluminum Stub Sills		
Rear Deck Height	41 Inches - Dropdeck (Plat/Chap/Titanium - Based on 22.5" Tires)		
Fifth Wheel Height	49 Inches		
King Pin	30 Inches		
Side Rail	Aluminum: 7.4" Ext w/ J-Hook Track and Heavy Duty Continuous Contact Rub Rail		
Extra Stake Pockets	None	Pair Qty	0
Conspicuity Tape	Conspicuity Tape on Side Rail		
Front & Rear Plates	FRONT: Alum Bev Cnr NO-Stake Pkts - REAR: Alum NO-Stake Pkts & Rubrail		
Flag Holders	None		

Rubber Dock Bumpers	Rubber Dock Bumpers on Rear Sill	
Drop Plate	23" Aluminum Drop Plate (Chap on 22.5")	
Knee Braces	None.	
Paint	Aluminum Trailer: Susp & Axles are Undercoated, LG/FW painted Silver	
Flooring	Aluminum Floor W/ 3 Apitong Nailers	
Load Hook Flooring	No Load Hook Track in Floor	
Landing Gear	Jost AX150 Aluminum (10 Year Warranty, 5 Year No Lube) - Handle: Road	
Rear Enclosure	Open Aluminum Rearend - Lights In Rear Sill	
PERIMETER BEAM OPTIONS	No Options Selected - Perimeter Beam Options May be Grouped	
OILFIELD OPTIONS	No Options Selected - Oilfield Options May be Grouped	
STRUCTURAL OPTIONS	No Options Selected - Structural Options May be Grouped	
SUSPENSIONS & AXLES	GAWR: 20,280 #	2
Suspension Type	Air Ride Suspension - Hendrickson -- AA230 (Intraax)	Axles on this Configuration
Axle Type	Hendrickson 23k Integrated RTR Axle - HXL5	
Number of Axles	2 Axles - Standard	
		Will have holes in main beams for slider pins so can easily be monitored
Sliding Axles	Dropdeck - Rear Axle Slide - Pins Through Internal Slider Tube	
Axle Spacing	61/122 Inches - For Rear Slider	Inches 0
Overhang	Determined by California Legal - Min. Overhang Est.: 63 Inche	Inches 0
Cal & Can Legal	California Legal	
Steerable Axle	None	
Lift Kits	None	
Axle Straps	None	
Axle Spindle Type	N-Type (All Axles)	
Brake Type	Drum Brakes - Spring brakes with auto slack adjusters	
Hub Type	Cast - Hub Piloted	
Drum Type	Cast	
Brake Dust Covers	None	
Bearing Lubricant	Synthetic Semi Fluid Solid Grease	
Hub-O-Meter	None	
Inflation Sys & Crossfires	None	
Mudflaps	One Pair Per Axle	
TIRES & WHEELS		8 Wheels and Tires in this Configuration
Tires	Gladiator (Tier 3) 255/70R22.5 (H) - QR40ST - 120PSI	
Outer Wheels	22.5" Standard Duty Steel - White	

Inner Wheels

22.5" Standard Duty Steel - White

Spare Tire

None

Spare Wheel

None

Tire Carrier

None

LIGHTS

Rear Lights

3-3-3 Light Pattern - Center 3 are MicroDot Lights, Outers are 4" LED

Extra Row of Rear Light

None

Back-up Lights

None

Strobe Lights

None

Over Dimension Lights

None

Pair Qty[0]

Side Marker Lights

MicroDot Lights - Qty between 4 and 9 Pairs

Pair Qty[5]

Side Light Options

None

AIR & ELECTRICAL OPTIONS

Anti-lock Braking System

Meritor 4S/2M

Air & Electrical Connection

Standard Plus Extra 7-way in Front Plate with Harness PLUS 4-way in rear panel

Air Raise & Lower Valve

Air Raise & Lower Valve In An Aluminum Box (Mounted on Bracket)

ISO Type Aux 7 way on nose - Wired to Electric dump on rear axle

Dump Valve

Both Auto Dump & Electric Dump

Standard Steel air tank for air system

Pull Lanyards on Air Tanks

None

Electric dump on rear axle

Gauges And Scales

None

LOAD SECUREMENT

Options Selected - Load securement Options MUST be Ungrouped

Winch Track

Winch Track (Double L) on Roadside & Curbside (Integrated in Aluminum Side Rail)

Tie Bar

Aluminum Tie Bar on Roadside & Curbside

Fixed Winches

None

Qty[0]

Sliding Winches 1

Standard Sliding Winch - BLACK (Specify Qty)

Qty[12]

[1 Ea side top, 5 ea side lower

Sliding Winches 2

None

Qty[0]

Recessed Floor D-Rings

None

Pair Qty[0]

Chain Ties

Recessed Chain Ties - Bolt-on (Specify Qty in Pairs in space to

Pair Qty[17]

[

Rope Hooks

None

Pair Qty[0]

C & G - Hooks

None

Qty[0]

J-Hooks

None

Qty[0]

J-Hook Carriers

None

Qty[0]

Container Locks

None

Load Bunks

None

Qty[0]

Bulkheads

None

No Options Selected - Box Options May be Grouped

BOXES

Tool Boxes: Type 1

None

Door: None

Locks: None

Qty[0]

Tool Boxes: Type 2

None

Door: None

Locks: None

Qty[0]

Gooseneck Boxes

None

Belly Boxes

None

Racks

None

DOVETAILS & RAMPS

No Options Selected - Dovetail Options May be Grouped

MISCELLANEOUS

Certificate Holder

Certificate Holders

FHWA Inspection

FHWA Inspection

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.