



A033454-A033458
VIN: 007188-077192

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Item	Series: TRANSPORT	Description	Model: ALUMINUM-BITUMINOUS
TANK CONSTRUCTION		ARA	
NOMINAL CAPACITY		7,500 GALLONS	
OVERALL TRAILER LENGTH		43'	
CODE		49 CFR 173.247	
DESIGN PRESSURE		ATMOSPHERIC	
VENTING		ASPHALT TYPE, LIGHT WEIGHT STYLE	
TEMPERATURE RATING		375 DEGREES	
MATERIAL-BARREL		5454-H32 ALUMINUM	
BAFFLES		(2) ALUMINUM	
COMPARTMENTS		ONE	
CAPACITY MARKERS		3-DISC	
INSULATION		4" FIBERGLASS, 1# DENSITY, NOT COMPRESSED	
ALUMINUM JACKETING		0.040" SIDE SHEETS/0.060" HEADS	
FRONT PUMP-OFF VALVE		3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING WITH A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT FENDER.	
REAR DISCHARGE VALVE		6" VALVE W/ 4" LINE TERMINATING WITH A 4" X 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTIONS	
GATE VALVE		4" AT REAR UNLOADING LINE	
THERMOMETER		3" DIAL IN WELL W/ PLEXIGLASS COVER ON SIDE OF TANK	
MANHOLE		20" QUICK OPENING, ASPHALT TYPE	
MANHOLE PLATFORM		4 SIDED, ALUMINUM	
DEFLECTOR PAN		BENEATH MANHOLE	
MANHOLE OVERFLOW		2" EXTERNAL	
HEATING SYSTEM		NONE	
LADDER		ALUMINUM, CURBSIDE	
WALKWAY		NONE	
EXTRA WIDE HOSE TROUGH		12" WIDE	
TIRE CARRIER		NONE	
FRONT FENDERS		ALUMINUM. MANUAL HOLDER ON FRONT ROADSIDE FENDER	
REAR FENDERS		ALUMINUM	
MUDFLAPS		ON REAR FENDERS AT REAR (REAR AXLE ONLY)	
LIGHTS		L.E.D. TYPE WITH ALUMINUM LIGHT BOXES AT REAR	
GLAD HANDS		LOW MOUNT, ON ROADSIDE	
AIR AND ELECTRICAL LINES		ROUTED OVER ROADSIDE FRONT FENDER	
BUMPER-SPLIT TYPE			
CONSPICUITY MARKING		PER DOT REQUIREMENTS	
UPPER COUPLER		ADJUSTABLE	
LANDING LEGS		2-SPEED, CURBSIDE CRANK WITH HORIZONTAL BRACE BETWEEN LANDING LEGS	



LANDING LEG FRAME	ALUMINUM
BOGIE	ALUMINUM
SUSPENSION	INTRAAAX AANT23K AIR RIDE TANDEM W/MANUAL EXHAUST MOUNTED ON REAR CROSSMEMBER
SUSPENSION	INSTALL LIFT BRACKETS ON SUSPENSION ARMS FOR FUTURE ADDITION OF LIFT KIT, FRONT AXLE
WHEEL END PACKAGE	HXL5 (5 YEAR WARRANTY)
AIR BRAKES	16.5" X 7" W/AUTO SLACKS, DUST SHIELDS, AND CENTRIFUSE DRUMS
ANTI-LOCK BRAKES	4S/2M SYSTEM (4 SENSORS/2 MODULATORS)
AXLE SPACING	50"
AXLE TRACK WIDTH	71 1/2"
HUBS	DURA-LIGHT
ALUMINUM DISC WHEELS	ACCURIDE 10-HOLE, HUB PILOTED, STANDARD POLISHED.
TIRES	11R22.5 (G)
PAINT	STEEL PARTS ONLY-GLOSS BLACK
CENTER PAINT BAND	14' WIDE BAND-BLACK
PLACARD KIT	SLIDE-IN TYPE W/ "HOT" PLACARD, 4 SIDES
SAMPLE VALVE	3/4"

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.