

# HALE

## TRAILER

### BRAKE & WHEEL



A033467-A033476  
VIN: S032296-S032305

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer   
**800-232-6535** \*FINANCING AVAILABLE

#### Fusion Flat 48' Air Slider (Model Code: HAFGF12SAT)

**Length / Width:** 48 feet x 102 inches

**Suspension Type:** Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

**Frame Rating:** 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

**Flooring:** 1 1/8 inch wood

**Crossmembers:** 12 inch centers - 4 inch jr. I-steel Galvanized

**Side Rails:** Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

**Stake Pockets:** Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

**Rubrail:** Integrated with siderail

**Main Beams:** High Tensile Steel load bearing flanges - Galvanized

**Kingpin:** 30 inches

**Loaded Fifth Wheel Height:** 49 inches

**Landing Gear:** OEM Standard Painted Black; Forward & Rear Bracing

**Knee Braces:** Fabricated on approx. 60 inch C/C - Galvanized

**Bulkhead Pockets:** 4 DOT type bulkhead pockets only - welded to front

**Bulkheads:** Removable aluminum 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets

**Number of Axles:** 2

**Axle Spindle:** Tapered

**Brakes:** Spring brakes, auto slacks; **Aluminum Air Tank**

**Air Line Filters:** (2) Meritor In-line type installed

**ABS:** 2S/1M BASIC - no cable or tool (\*Fontaine recommends 4S/2M)

**Axle Spread:** 49 inches

**Hub and Drums:** 10-hole hub-piloted with outboard cast drums

**Wheel Ends:** Grease in hubs - \*\*\* 5-year wheel end warranty \*\*\*

**Wheels:** 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

**Tires:** 11R 22.5 14PR OEM standard tires

**Tire Inflation System:** None standard

**Suspension Detail:** Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable Painted Black

**Air Assist Slide Box Pins:** Standard mount of controls on slider frame

**Auto Glad Hand Dump :** Installed

**Front Corners:** Tapered steel

**Electrical System:** LED: 3 lights/side, 3 lights/side on rear - STANDARD

**Paint:** Galvanized Frame with Fontaine Fusion Decals

**Conspicuity Tape:** Per NHTSA specs - installed in recess on rubrails

**Bumper:** Weld-on type - meets underride requirements

**Mudflaps:** 1 set OEM standard behind rear axle

**Spare Tire Carrier:** None standard

**Winch Track:** Full length integrated double L type aluminum on both sides -- STANDARD

**Sliding Winches:** 12: 6 each side ZINC with sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD

**27 foot Winch Straps:** None standard

**30 foot Winch Straps:** None standard

**Dock Bumpers:** 1 pair rubber on rear

**Hubodometer:** None standard

**Registration Holder:** Install registration holder - OEM standard

**Tool Box:** None standard

**VIN Plate:** Bilingual US/Canadian VIN plate

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.