





A033478-A033502
VIN: S032306-S032330



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, STEEL PLATFORM LEGEND SD
DIMENSIONS	
LENGTH	48'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 59 1/2" high at front and 54" at rear.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	30" from front.
COUPLER HEIGHT	48".
STRUCTURE	44" c/c frame with "CAMBER".
FLANGES	3/8" x 5", high tensile.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 27" high at the peak. with holes, parachute shaped, to lighten trailer.
GOOSENECK	11 1/4" high, with integrated nose ramp and 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Screws
SIDE RAILS	10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets.
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
X BRACES	Between main beams, full length.
ENDS	
FRONT RAIL	Formed steel, bolted.
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground.
HEADBOARD	48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. (this bulkhead is NOT D.O.T.) *** Galvanized ***
POCKETS	2 bolted galvanised pockets at front for removable headboard.
BUMPER	2 rubber dock, at the end of rear rail.
REAR RAIL	Formed steel.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560).
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light.
FLASHERS	Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.
TAIL LIGHTS	Sealed beams (Grote DEL #54332) red. Qty: 1 additionnal each side.



ITEM	DESCRIPTION
	From outside, tail lights and flasher, flasher with parking, brake with parking.
LANDING GEAR SAND SHOES CRANK	Holland, ATLAS 55 (LG4421) 10" x 10". Road side.
BOGIE BASIC MECHANICAL BOGIE	Slider, Hutch H-9000, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension. 6" c/c between locating holes, (48" travel).
MECHANICAL (GROUND AXLES) SUSPENSION U-BOLTS SPRINGS AXLE(S) CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES	Hutch H-9700, tandem, under mount, 49" spread. With nuts at bottom. 3 leaves, model TRA 2741, 12 000 lbs capacity. Meritor, TN 467_L, 22 500 lbs. capacity. 28 splines. 77 1/2". None (Meritor axles). 16 1/2" standard, FRAS-LE MA212Q+ extended life lining. HM 218248 and HM 212049 TSE S-ASA, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omni brake" (30-30). (4 years warranty by T.S.E. for parts only). 10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Doublecoin, 11 R 22.5 TR100 14 ply (41.0")
AIR SYSTEM GLAD HANDS AIR VALVES	With filter. Meritor Wabco, IABS, 2 sensors 1 modulator.
ACCESSORIES REGISTRATION HOLDER MUD FLAPS SLIDING TRACK WINCHES	One plastic, Betts-PS-1 or equivalent. One set, rubber with moose logo and vertical grooves to reduce spray. Full length, "LL" extruded aluminum, road side. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8").
FINISHING PAINT BOGIE	Shot blasted, one coat of epoxy primer and one acrylic polyurethane top coats Color: black, code: PPG CCA947255-55. One coat of epoxy primer and one acrylic urethane top coats, Color: black, code: PPG CCA947255-55. Axles (wheel end) included. (Tandem).



ITEM	DESCRIPTION
RETROREFLECTIVE TAPES	Axle line type: Color: black, code: PPG CCA947255-55.
WHEELS OR RIMS	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
ADDITIONAL OPTIONS	White (power top coat).
CONFORMITY	same as U#238175 estimated weight is 12,000 LBS +/- 3%
	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.
DISCLAIMER	
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.	
Equipment availability, prices and specifications are subject to change without notice.	