

HALE

TRAILER

BRAKE & WHEEL



A033546-A033570
VIN: S032372-S032396

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Infinity Flat 48' Air Slider (Model Code: HAICF12SAT)

Length / Width: 48 feet x 102 inches
Suspension Type: Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips
Crossmembers: 12 inch centers - 4 inch jr. I-steel
Single Coil Hauling Package: Included
Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
Chain Cargo Tie Downs: None included
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
Rubrail: Integrated with siderail
Main Beams: 130K load bearing flanges
Kingpin: 30 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM Standard with Forward & Rear Bracing
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front
Bulkheads: Removable Aluminum 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets
Number of Axles: 2
Axle Spindle: Tapered
Brakes: Spring brakes, auto slacks; Aluminum Air Tank
Air Line Filters: (2) Meritor In-line type installed
ABS: 2S/1M BASIC - no cable or tool
Axle Spread: 49 inches
Hub and Drums: 10-hole hub-piloted with outboard cast drums
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
Tires: 11R 22.5 14PR OEM standard tires
Tire Inflation System: None standard
Suspension Detail: Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable
Air Assist Slide Box Pins: Standard mount of controls on slider frame
Auto Glad Hand Dump : Installed
Front Corners: Tapered steel
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD
Paint: Black urethane on steel parts with Infinity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails
Bumper: Weld-on type - meets override requirements - painted steel
Mudflaps: 1 set OEM standard behind rear axle
Spare Tire Carrier: None standard
Winch Track: Full length integrated double L type aluminum on both sides -- STANDARD
Sliding Winches: 15 Zinc Finish: 8 road side, 7 curb side; sliding Rope Hook/ Winch Strap Hook Retainers
27 foot Winch Straps: None standard
30 foot Winch Straps: None standard
Dock Bumpers: 1 pair rubber on rear
Hubodometer: None standard
Registration Holder: Install registration holder - OEM standard
Tool Box: None standard
VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.