



A033604-A033612

VIN: S032430-S032438

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Infinity Flat 48' Wide Spread Air
(Model Code: HAICF12WSA)

Length / Width:	48 feet x 102 inches
Suspension Type:	Wide spread air
Frame Rating:	80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads
Flooring:	1 1/8 inch aluminum with 4 wood nailer strips
Crossmembers:	12 inch centers - 4 inch jr. I-steel
Single Coil Hauling Package:	Included
Side Rails:	Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
Chain Cargo Tie Downs:	None included
Stake Pockets:	Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
Rubrail:	Integrated with siderail
Main Beams:	130K load bearing flanges
Kingpin:	30 inches
Loaded Fifth Wheel Height:	49 inches
Landing Gear:	OEM Standard with Forward & Rear Bracing
Knee Braces:	Fabricated on approx. 60 inch C/C
Bulkhead Pockets:	4 DOT type bulkhead pockets only - welded to front
Bulkheads:	Removable Aluminum 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets
Number of Axles:	2
Axle Spindle:	Tapered
Brakes:	Spring brakes, auto slacks
Air Line Filters:	(2) Meritor In-line type installed
ABS:	2S/1M BASIC With Sensors Installed on Rear Axle Should Front Axle be Lifted- no cable or tool
Axle Spread:	122 inches - set at rear
Hub and Drums:	10-hole hub-piloted with outboard cast drums
Wheel Ends:	Grease in hubs - *** 5-year wheel end warranty ***
Wheels:	22.5 x 8.25 4 steel disc inside wheels - 4 aluminum High Polish outside with 4 Spacers
Tires:	11R 22.5 14PR OEM standard tires
Tire Inflation System:	None standard
Suspension Detail:	Hendrickson AANT23K Intraax air ride
Auto Glad Hand Dump :	Installed
Electric Dump Valve:	Wired to 7-way auxiliary socket to dump rear axle
Air Lift:	Lift Not Included: *On Front Axle Only Install Hendrickson UBL-005 Front Bolt-on Suspension Hanger Brackets (LH C-30293-1C & RH C-30293-2C) & Weld-on Lift Brackets (LH C-30209-1C & RH C-30209-2C); Install Appropriate K-Brace To Fit Around These Brackets (**HALE TRAILER WILL FURNISH AND INSTALL (2) C-23114 Air Springs in Addition to other required plumbing and Lift axle Control Components)
Front Corners:	Tapered steel
Electrical System:	LED: 3 lights/side, 3 lights/side on rear - STANDARD
Paint:	Black urethane on steel parts with Infinity decals - STANDARD
Conspicuity Tape:	Per NHTSA specs - installed in recess on rubrails
Bumper:	Weld-on type - meets underride requirements - painted steel
Mudflaps:	2 sets OEM standard; Spring loaded brackets behind front axle
Spare Tire Carrier:	None standard
Winch Track:	Full length integrated double L type aluminum on both sides -- STANDARD
Sliding Winches:	(15) ZINC Finish: 8 Road Side, 7 Curb Side with Sliding Rope Hook/Winch Strap Hook Retainers
27 foot Winch Straps:	None standard
30 foot Winch Straps:	None standard
Dock Bumpers:	1 pair rubber on rear
Hubodometer:	None standard
Registration Holder:	Install registration holder - OEM standard
Tool Box:	1 CAM LOCK aluminum double door box - 24 inches x 24 inches x 60 inches - installed Road Side between spread axles
VIN Plate:	Bilingual US/Canadian VIN plate
Please Note:	Price includes commodity surcharges
Unit Numbers & Decals:	Not installed
Stacking:	Price includes Standard stacking of each trailer

Fontaine Select to Install 4 Extra Pair Side MARKER LIGHTS (*Total 7 Lights Ea. Side)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.