



A033682-A033686 VIN: S032507-S032511

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: Springfield, MA: 888-673-5011 800-854-5306

Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer (f) 😉 🛅 🎯

800-232-6535 *FINANCING AVAILABLE

Infinity Low Deck Height Drop Deck 53' Rear Axle Slide Air (Model Code: HAILD22RSA)

Length / Width: 53 feet x 102 inches Suspension Type: Rear axle slide

Deck Lengths: 11 feet front and 42 feet rear

Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Rear Deck Height: 36 inches - loaded, 37 inches unloaded Flooring: 1 1/8 inch aluminum with 4 wood nailer strips

Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

Single Coil Hauling Package: Included

Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact

Chain Cargo Tie Downs: None included

Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

Rubrail: Integrated with siderail

Main Beams: 130K load bearing flanges

Kingpin: 30 inches

Fifth Wheel Height: 49 inches **Landing Gear:** OEM standard

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front

Bulkheads: None standard Number of Axles: 2 Axle Spindle: Tapered

Brakes: 12 1/4" X 7 1/2"; Spring brakes; auto slacks; Linings for 20,000# GAWR; Aluminum Air Tank

Air Line Filters: (2) Meritor In-line type installed

ABS: 2S/1M - no cable or tool

Axle Spread: 122 inches open - 61 inches closed: Meets California, Canadian RTAC and BC dimensional specifications in closed position

Hub and Drums: 8-hole hub-piloted with outboard cast drums **Wheel Ends:** Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 17.5 x 6.75 4 steel disc inside wheels - 4 outside aluminum LvL One Buffed with 4 Spacers

Tires: 245/70R 17.5 18PR Michelin XTA2 Energy (20,000# GAWR)

Tire Inflation System: Hendrickson TIREMAAX PRO

Suspension Detail: Hendrickson HT250US and HTZUS air ride

Air Assist Slide Box Pins: Standard mount of controls on slider frame

Auto Glad Hand Dump: Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Front Corners: Tapered

Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD

Paint: Black urethane on steel parts with Infinity decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails and rear bumper

Bumper: Weld-on type - meets underride requirements - painted steel

Mudflaps: 1 set OEM standard behind rear axle only

Winch Track: Full length integrated double L type aluminum on both sides where possible -- STANDARD

Sliding Winches: 15 total Zinc Finish, 3 front deck and 12 rear deck: 8 road side, 7 curb side; sliding Rope Hook/ Winch Strap Hook Retainers

27 foot Winch Straps: None standard
30 foot Winch Straps: None standard
Dock Bumpers: 1 pair rubber on rear

Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: 1 CAM LOCK aluminum double door box - 18 inches x 18 inches x 60 inches - installed Road Side

VIN Plate: Bilingual US/Canadian VIN plate

Please Note: Price includes commodity surcharges

Unit Numbers & Decals: Not installed