

HALE TRAILER BRAKE & WHEEL



A033961-A033968

VIN: 66304-66311

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

We propose to furnish the following described equipment, material and services at prices, terms and delivery set forth below:

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 48' Length, 16.2 Units

STANDARD SPECIFICATIONS: CTSSF-48 (South Specs) **2027 Model**

Type: Peerless dual axle, transport semi-trailer, **45 degree front**

Design: Box design, flat floor, end dump, live floor

Construction: **Skin stressed .063 natural aluminum with aluminum interior posts (14.5" centers)**
Skins to extend to bottom of lower rail

Unloading Time: Approximately 8 minutes

Capacity: 16.2 units (119.8 cu yd)

Dimensions: **48' long, 8' 6" wide, 13' 3" high**, 37" king pin location, 36" rear axle from rear of trailer

Tires: Eight (8) **11:00 x 24.5 radial tires**

Wheels: Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile **steel, Unimount**

Axles: 25,000# cap. inserted spindles, **77 1/2" track**, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks

Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system

A.B.S.: 2 sensor - 1 module

Suspension: Four spring three leaf tandem (**Hutch H9700T with slider**)

Landing Gear: Two speed, crank on driver's side (**Holland Atlas 55**), channel bracing

King Pin: Standard SAE, heat treated, **37" setting, 49" height, 3 I-beams with 5/16" plate**

Cross Sills & Decking: **Keith "New Style" Horizontal Seal 7/32" x 4.313" slats with wear strips**, 3" cylinder, rubber seals, standard live floor, **4" Jr. I-Beams on 22" centers** with aluminum sub-deck, wear strips on one end

Top: Flat design, open top, single center tie

Top Cover: **Shur-lok roll over tarp, vinyl material black in color, rear crank**

Tarp Bows: **Nine (9) flat bows spaced out evenly**

Rear Door: Full opening, **side hinged, solid freight door with four (4) latches, low mount, offset hinges**

Dump Stands: Two (2) blades at rear for standard Peerless backstop

Screens: **Safety screens on front and under drive**

Ladders: **One located at front and one located at rear**

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt, air and light plugs on front center

Lights: Six (6) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights **all lights to be LED, reverse lights ran to toggle switch on driver side of head board**

Glad Hands: Standard mounted on road side of headboard, **w/ in-line air filter**

Reflectors: Legal DOT

Paint: Aluminum natural, **steel components primed and painted BLACK**

Weight: Approximately 14,300# (+/- 3%)

REF#: 66210 (same as except changes in red)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.